

Sundance Spas

Aspen[®] Maxxus[™] Optima[®] Cameo[®] Altamar[®] Cambria[™] Marin[®] Capri[®]

Attention New Hot Tub Owner!

Congratulations on the purchase of your new Sundance[®] hot tub! The following is a list of automated functions performed by your hot tub. These functions are listed below in an attempt to suppress any operational concerns you may have during the first 24 hours of ownership! Also listed below are important maintenance recommendations you should observe on a regular basis to protect your new investment.

Maintain Healthy Spa Water

Always maintain your hot tub's water chemistry within the following parameters:

	With CLEARRAY®	Without CLEARRAY®
pH	7.4-7.6	7.4-7.6
Free chlorine	no less than 1.0 ppm	3.0-4.0 ppm
Free Bromine	no less than 2.0 ppm	2.0-4.0 ppm
Total Alkalinity	100-150 ppm	100-150 ppm
Calcium Hardness	150-250 ppm	150-250 ppm

IMPORTANT: CLEAR**RAY**® Water Purification System is factory installed. If the CLEAR**RAY**® system is altered or is not operating efficiently follow the "without CLEAR**RAY**®" water chemistry parameters. Such parameters are defined by the Association of Pool and Spa Professionals. CLEAR**RAY**® requires an annual lamp replacement to properly sanitize your water.

TO DECREASE RISK OF INFECTION OR DISEASE! Always maintain your spa filter as outlined below to ensure healthy spa water. Refer to pages 69-71 for additional information.

Required Filter Maintenance

Your new hot tub is equipped with an advanced MicroClean® Ultra water filtration system that provides unsurpassed water quality! To ensure maximum water quality at all times, you should replace the filter cartridge every six months, or earlier as necessary. The filter cartridge is designed to be thrown away! Attempts to reuse the filter cartridge may result in the re-release of unwanted particles back into the hot tub. See pages 69-71 for detailed filter cartridge replacement instructions.

Required Water Replacement

TO DECREASE RISK OF INFECTION OR DISEASE! You should replace the hot tub's water every 3 to 6 months. The frequency depends on a number of variables including frequency of use, number of users, and attention paid to water quality maintenance. You will know it is time for a change when you cannot control sudsing and/or you can no longer get the normal feel or sparkle to the water, even though the key water balance measurements are all within the proper parameters. See pages 77-79 for additional information.

1.0 2.0	Important Hot Tub Owner Information FCC Notice	1
3.0	Important Safety Instructions for all Spa Owners	
3.1	Entrapment Risk	- 7
3.2	Hyperthermia	
3.3	Important Additional Safety Instructions	
4.0	Locating Your Sundance Hot Tub	9
4.1 4.2	Outdoor Location	
5.0	General Electrical Safety Instructions	12
6.0 7.0	Electrical Installation Instructions (240V Service) Power Requirements	13
8.0	Hot Tub Fill Up Procedure	17
9.0	Hot Tub Features	
9.1	Maxxus™ Hot Tub Features	
9.2	Maxxus Massage/Waterfall Selector Diagram	
9.3 9.4	Maxxus Air Controls DiagramAspen® Hot Tub Features	
9. 4 9.5	Aspen Massage/Waterfall Selector Diagram	20
9.6	Aspen Air Controls Diagram	27
9.7	Optima® Hot Tub Features	
9.8	Optima Massage/Waterfall Selector Diagram	
9.9	Optima Air Controls Diagram	
9.10	Cameo® Hot Tub Features	
9.11	Cameo Massage/Waterfall Selector Diagram	
9.12 9.13	Cameo Air Controls Diagram	
9.14	Altamar Massage/Waterfall Selector Diagram	
9.15	Altamar Air Controls Diagram	
9.16	Marin® Hot Tub Features	
9.17	Marin Massage/Waterfall Selector Diagram	38
9.18	Marin Air Controls Diagram	
9.19	Cambria™ Hot Tub Features	
9.20	Cambria Massage/Waterfall Selector Diagram	
9.21 9.22	Cambria Air Controls Diagram Capri® Hot Tub Features	42
9.22 9.23	Capri Massage/Waterfall Selector Diagram	43
9.24	Capri Air Controls Diagram	
10.0	Registration and Start-up	
10.1	Start-up Sequence	46
10.2	Register Your New Spa	46
10.3	iTouch™ Control Panel Main Menu	47

48
48
49
50
52
53
53
54
54
54
55
55
55
55 56
56 56
50
57
58
59
60
61
61
62
64
65
66
67
68
68
69
69
71
73
74
74
75
/b
75 75
75 75 76

14.0	Water Quality Maintenance	77
14.1	pH Control	78
14.2	Sanitizing	
14.3	CLEARRAY® Water Purification System	79
14.4	CLEARRAY® Bulb Replacement and Quartz	
	Tube Maintenance	80
14.5	Other Additives	82
14.6	Handrail Maintenance	
15.0	Troubleshooting - Display Messages	83
16.0	Troubleshooting - Procedures	
17.0	Typical Hot Tub Wiring Diagrams A-B	
	(North American 60 Hz Models Only)	89
	(North Amorroan of the models of hy)	
18.0	North American 60 Hz Electrical Wiring Diagram	90
18.1	North American 60 Hz 3-Pump Models Electrical	
	Wiring Diagram	90
18.2	North American 60 Hz 1- and 2-Pump Models	
	Electrical Wiring Diagram	91
18.3	Dip Switch Settings	
•	=	· · · · · · · · · · · · · · · · · · ·

1.0 Important Hot Tub Owner Information

Your Sundance® hot tub is constructed to the highest standards and is capable of providing many years of trouble-free use. However, because heat retentive materials are utilized to insulate the hot tub for efficient operation, an uncovered hot tub surface and wall fittings directly exposed to sunlight and high temperatures for an extended period are subject to permanent damage or discoloration. Damage caused by exposing the hot tub to this abuse is not covered under warranty. We recommend that you always keep the hot tub full of water when it is exposed to direct sunlight and that you keep the Sundance insulating cover in place at all times when the hot tub is not in use. Read and carefully follow the requirements for your hot tub's support base found in the Section 4.0 titled, "Locating Your Sundance Hot Tub" (page 9) or as prescribed by your authorized Sundance Spas dealer.

Sundance hot tubs constantly strives to offer the finest hot tubs available, therefore, modifications and enhancements may be made which affect the specifications, illustrations and/or instructions contained herein.

2.0 FCC Notice

This equipment has been tested and found to comply with the limits for a Class B Digital Device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Rearrange or relocate the receiving antenna;
- 2. Increase the separation between the equipment and receiver;
- 3. Connect the equipment into an outlet on a circuit different from the circuit connected:
- 4. Consult the dealer or an experienced radio/TV technician for help. (Changes or modifications not expressly approved by the party responsible for FCC compliance could void the user's authority to operate this equipment).

3.0 Important Safety Instructions for all Spa Owners

READ AND FOLLOW ALL INSTRUCTIONS CAREFULLY!

This spa was manufactured to meet the standards and specifications outlined in the "Virginia Graeme Baker Pool and Spa Safety Act" (VGB Safety Act). When installing and using this spa, basic safety precautions should always be followed, including:

1. A DANGER: RISK OF SEVERE INJURY OR DROWNING!

- Extreme caution must be exercised to prevent unauthorized access by children.
- To avoid accidents, ensure that children do not use this spa unless supervised at all times. Adult supervision is a critical safety factor in preventing children from drowning.
- Use the straps and clip tie downs to secure the spa cover when not in use. This will help discourage unsupervised children from entering the spa. Keep the spa cover secure in high-wind conditions.
- There is no representation that the cover, clip tie-downs, or actual locks will prevent access to the spa.

2. PANGER: RISK OF SEVERE INJURY OR DROWNING!

- Keep hair, loose articles of clothing or hanging jewelry away from suction fittings, rotating jets or other moving components to avoid entrapment that could lead to drowning or severe injury.
- Never use the spa unless all suction guards, filter, filter lid, or skimmer assembly are installed to prevent body and/or hair entrapment.
- Never operate or use the spa if the filter, filter lid, or skimmer assembly are broken or any part of the skimmer assembly is missing. Please contact your dealer or nearest service center for service.
- The suction fittings and suction covers in this spa are sized to match the specific water flow created by the pump(s). If it is necessary to replace the suction fittings, suction covers or pump(s), be sure that the flow rates are compatible and are in compliance with the VGB Safety Act.
- Never replace a suction fitting or suction cover with one rated less than the flow rate marked on the original suction fitting. Using improper suction fittings or suction covers can create a body or hair suction entrapment hazard that may lead to drowning or severe injury.

3. PANGER: RISK OF SEVERE INJURY FROM ELECTRIC SHOCK OR DEATH FROM ELECTROCUTION!

Install the spa at least 5 feet (1.5m), from all metal surfaces. As an alternative, a spa may be installed within 5 feet of metal surfaces if each metal surface is permanently connected (bonded) by a minimum No. 8 AWG (8.4 mm²) solid copper conductor attached to the wire connector on the grounding lug, inside the equipment compartment on the equipment box.

- A grounding wire connector is provided on this unit to connect a minimum No. 8 AWG (8.4 mm²) solid copper conductor between this unit and any metal equipment, metal enclosures of electrical equipment, metal water pipe, or conduit within 5 feet (1.5m) of the unit.
- Never permit any electrical appliance, such as a light, telephone, radio, television, etc. within 5 feet (1.5m) of a spa unless such appliances are built-in by the manufacturer.
- Never bring any electrical appliances into or near the spa.
- Never operate any electrical appliances from inside the spa or when you are wet.
- The electrical supply for this product must include a suitably rated switch or circuit breaker to open all ungrounded supply conductors to comply with section 422-20 of the National Electrical Code/ USA, ANSI/NFPA 70. The disconnecting means must be readily accessible and visible to the spa occupant but installed at least 5 feet (1.5m), from the spa.
- The electrical circuit supplied for the hot tub must include a suitable ground fault circuit interrupter (GFCI) as required by NEC Article 680-42.

4. **WARNING:** RISK OF SEVERE INJURY OR DEATH!

- Extreme caution must be exercised to prevent diving or jumping into the spa or slipping and falling, which could result in unconsciousness, drowning, or serious injury. Remember that wet surfaces can be very slippery.
- Never stand, walk or sit on the top railing of the spa.

5. **WARNING:** RISK OF HYPERTHERMIA (OVER-HEATING) CAUSING SEVERE INJURY, BURNS, WELTS OR DEATH!

- Water temperature in excess of 104°F (40°C) may be injurious to your health.
- Refer to Section 3.2 Hyperthermia for specific causes and symptoms of this condition.
- The water in the spa should never exceed 104°F (40°C). Water temperatures between 100°F (38°C) and 104°F (40°C) are considered safe for a healthy adult.
- Lower water temperatures are recommended for young children (children are especially sensitive to hot water) and when spa use may exceed 10 minutes.
- The Consumer Products Safety Commission/USA has stated that the water temperature in a spa should not exceed 104°F (40°C).
- Always test the spa water temperature before entering the spa.
 The user should measure the water temperature with an accurate thermometer since the tolerance of water temperature-regulating devices may vary as much as +/- 5°F (2°C).

6. WARNING: RISK OF SEVERE INJURY OR DEATH!

- Since excessive water temperatures have a high potential for causing fetal damage during the early months of pregnancy, if pregnant or possibly pregnant, consult your physician before using a spa.
- Pregnant or possibly pregnant women should limit spa water temperatures to 100°F (38°C).
- Persons suffering from obesity or a medical history of heart disease, low or high blood pressure, circulatory system problems, diabetes, infectious diseases or immune deficiency syndromes should consult a physician before using a spa.
- If you experience breathing difficulties in association with using or operating your spa, discontinue use and consult your physician.
- Persons using medication should consult a physician before using a spa since some medication may induce drowsiness, while other medication may affect heart rate, blood pressure, and circulation.
- Persons suffering from any condition requiring medical treatment, the elderly, or infants should consult with a physician before using a spa.
- The use of alcohol, drugs, or medication before or during spa use may lead to unconsciousness with the possibility of drowning.

7. WARNING: RISK OF SEVERE INJURY OR DEATH!

- Prolonged immersion in a spa may be injurious to your health.
- Observe a reasonable time limit when using the spa. Exposures at higher temperatures can cause high body temperature (overheating). Symptoms may include dizziness, nausea, fainting, drowsiness, and reduced awareness. These effects could possibly result in drowning or serious injury.
- Never use a spa immediately following strenuous exercise. Enter and exit the spa slowly. Wet surfaces can be slippery.

8. VARNING: TO DECREASE RISK OF INFECTION OR DISEASE!

- To reduce the risk of contracting a waterborne illness (e.g. an infection, bacteria or virus) and/or respiratory ailments, maintain water chemistry within the parameters listed on the inside cover of this manual and consult with a licensed engineer regarding proper ventilation if installed indoors or in an enclosed area.
- People with infectious diseases should not use a spa to avoid water contamination, which could result in spreading infections to others.
- Always shower before and after using your spa. Maintain water chemistry in accordance with manufacturer's instructions. Failure to do so may result in contracting a waterborne illness (e.g. an infection, bacteria or virus).

9. WARNING: In addition to maintenance of filters and water chemistry, proper ventilation is recommended to reduce the risk of contracting a waterborne illness (e.g. an infection, bacteria or virus) and/or respiratory ailments that could be present in the air or water. Consult a licensed architect or building contractor to determine your specific needs if installing your hot tub indoors.

10. CAUTION: TO DECREASE RISK OF PRODUCT DAMAGE.

- Maintain water chemistry in accordance with manufacturer's instructions.
- Proper chemical maintenance of spa water is necessary to maintain safe water and prevent possible damage to spa components.
- 11. AND WARNING: RISK OF SEVERE INJURY OR DEATH!

 The appliance is not intended for use by persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience or knowledge, unless they have been given supervision or instruction concerning use of the appliance by a person
- 12. **NOTE:** This spa is not intended nor designed to be used in a commercial or public application. The spa buyer shall determine whether there are any code restrictions on the use or installation of this spa since local code requirements vary from one locality to another.

Hot Tub Safety Literature

To ensure you have a safe and enjoyable hot tub experience, learn all you can about hot tub safety and emergency procedures. Especially useful are the brochures listed below:

• Children Aren't Waterproof

responsible for their safety.

- Pool and Spa Emergency Procedures For Infants and Children
- Layers of Protection
- The Sensible Way to Enjoy Your Spa or Hot Tub

The Association of Pool and Spa Professionals publishes these brochures. To acquire a brochure:

- Ask your hot tub dealer (they may have copies)
- Go to http://www.apsp.org
- Conduct your own search on the internet
- Write to the following address:
 The Association of Pool and Spa Professionals 2111 Eisenhower Avenue Alexandria VA 22314 703.838.0083

FOR CALIFORNIA RESIDENTS ONLY NUR FÜR EINWOHNER KALIFORNIENS POUR LES RÉSIDENTS DE LA CALIFORNIE SEULEMENT PARA RESIDENTES DE CALIFORNIA ÚNICAMENTE



WARNING: Drilling, sawing, sanding or machining wood products can expose you to wood dust, a substance known to the State of California to cause cancer. Avoid inhaling wood dust or use a dust mask or other safeguards for personal protection. For more information go to www.p65Warnings.ca.gov/wood



ACHTUNG: Das Bohren, Sägen, Schleifen oder Zerspanen von Holzprodukten kann Stäube freisetzen. Diese Substanz gilt im US-Bundesstaat Kalifornien als krebserregend. Möglichst keinen Holzstaub einatmen bzw. eine Staubmaske oder anderweitige persönliche Schutzmaßnahmen einsetzen. Weitere Informationen finden Sie auf www.P65Warnings.ca.gov/wood



AVERTISSEMENT: Le forage, le sciage, le ponçage ou l'usinage des produits du bois peuvent vous exposer à la poussière de bois, une substance connue dans l'État de Californie pour causer le cancer. Éviter d'inhaler la poussière de bois ou utiliser un masque antipoussières ou d'autres mesures de protection personnelle. Pour de plus amples renseignements, consulter le site www.P65Warnings.ca.gov/wood



ADVERTENCIA: Perforar, cortar, lijar o usar máquinas con productos de madera le puede exponer a polvo de madera, una substancia reconocida por el Estado de California como causante de cáncer. Evite inhalar polvo de madera o utilice una máscara antipolvo u otros resguardos para protección personal. Para más información, visite www.P65Warnings.ca.gov/wood

6530-460 Rev A (12/18)

FOR CALIFORNIA RESIDENTS ONLY
NUR FÜR EINWOHNER KALIFORNIENS
POUR LES RÉSIDENTS DE LA CALIFORNIE SEULEMENT
PARA RESIDENTES DE CALIFORNIA ÚNICAMENTE



WARNING: Cancer and Reproductive Harm www.p65Warnings.ca.gov



ACHTUNG: Krebserregend und mit fortpflanzungsschädigender Wirkung-www.p65Warnings.ca.gov



AVERTISSEMENT: Cancer et danger pour la reproduction www.p65Warnings.ca.gov



ADVERTENCIA: Cáncer y daño reproductivo www.p65Warnings.ca.gov


6530-464 Rev A (12/18)

3.1 Entrapment Risk

The Consumer Products Safety Commission/USA has reported that users of pools and spas have become entrapped (stuck) to drain and/or suction fittings causing death, drowning, or serious injury (see diagram below). This spa was manufactured to meet the standards and specifications outlined in the "Virginia Graeme Baker Pool and Spa Safety Act" (VGB Safety Act). Entrapment risk can be minimized if proper precautions are taken.



DANGER: RISK OF PERSONAL INJURY OR DEATH! Never operate the spa if a suction fitting, suction cover, filter, filter lid or skimmer assembly are broken, damaged or missing.



NOTE: SUCTION COVERS MUST BE REPLACED EVERY 7 YEARS.

- 1. DANGER: RISK OF SEVERE INJURY OR DROWNING!
 Hair entrapment: May occur if hair is entangled, knotted or snagged in a drain suction or skimmer assembly. This has been reported in persons who when submerge themselves underwater, allowing hair to come close and/or within the reach of the suction fittings, suction covers or skimmer assembly.
- Keep hair away from suction fittings, suction covers, filter, filter lid or skimmer assembly.
- Children are at risk for hair entrapment if swimming under water.
- Never allow children to play or get near the suction fittings, suction covers, filter, filter lid or skimmer assembly.
- 2. DANGER: RISK OF SEVERE INJURY OR DROWNING! Limb entrapment: May occur when a limb becomes entrapped, inserted or sucked into a suction or outlet opening.
- Always keep suction fittings, suction covers, filter, filter lid or skimmer assembly in place when operating to avoid limb entrapment.
- Never allow children to play or get near the suction fittings, suction covers, filter, filter lid or skimmer assembly.

- 3. DANGER: RISK OF SEVERE INJURY OR DROWNING!
 Body entrapment: May occur when part of the torso becomes entrapped, inserted or sucked into a suction or outlet opening.
- Never allow children to play or get near the suction fittings, suction covers, filter, filter lid or skimmer assembly.
- 4. DANGER: RISK OF SEVERE INJURY OR DROWNING! Evisceration (disembowelment) entrapment: May occur when the buttocks becomes entrapped, inserted or sucked into a suction or outlet opening.
- Never sit on suction fittings, suction covers, filter, filter lid or skimmer assembly.
- Never allow children to play or get near the suction fittings, suction covers, filter, filter lid or skimmer assembly.
- 5. DANGER: RISK OF SEVERE INJURY OR DROWNING!
 Mechanical entrapment: May occur when jewelry, swimsuit, or
 hair accessories become entangled, knotted or snagged in a drain
 suction or skimmer assembly.
- Never allow your jewelry, swimsuit, or hair accessories to come close to the suction fittings, suction covers or skimmer assembly.
- Never allow children to play or get near the suction fittings, suction covers, filter, filter lid or skimmer assembly.

3.2 Hyperthermia

Prolonged immersion in hot water may induce hyperthermia (overheating). The use of alcohol or drugs can greatly increase the risk of fatal hyperthermia in spas. A description of the causes, symptoms, and effects of hyperthermia are as follows:

Hyperthermia occurs when the internal temperature of the body reaches a level several degrees above the normal body temperature of 98.6°F (37°C). The symptoms of hyperthermia include drowsiness, lethargy (fatigue), and an increase in the internal temperature of the body (feeling of being too hot). The effects of hyperthermia include:

- Unawareness of impending hazard;
- Failure to perceive heat;
- Failure to recognize the need to exit spa;
- Physical inability to exit spa;
- · Fetal damage in pregnant women; and
- Unconsciousness and danger of drowning.

A Warning Sign is provided in your warranty packet. Please install at a location near your spa, where it is visible to users of the spa. For additional or replacement Warning Signs please contact your local Sundance spas dealer and reference item number #6530-082.

3.3 Important Additional Safety Instructions

When using this electrical equipment, basic safety precautions should always be followed, including the following:

1. READ AND FOLLOW ALL INSTRUCTIONS.

- 2. A green colored terminal or a terminal marked G, Gr, Ground, Grounding or the ⊕ symbol* is located inside the supply terminal box or compartment. To reduce the risk of electric shock, this terminal must be connected to the grounding means provided in the electric supply service panel with a continuous copper wire equivalent in size to the circuit conductors that supply this equipment (*IEC Publication 417, Symbol 5019).
- At least two lugs marked "Bonding Lugs" are provided on the external surface or on the inside of the supply terminal box/compartment.
 To reduce the risk of electric shock, connect the local common bonding grid in the area of the spa to these terminals with an insulated or bare copper conductor not smaller than No. 6 AWG (10 mm²).
- All field installed metal components such as rails, ladders, drains or other similar hardware within 10 feet (3m) of the spa shall be bonded to the equipment grounding buss with copper conductors not smaller than No. 6 AWG (10 mm²).
- 5. SAVE THESE INSTRUCTIONS.

4.0 Locating Your Sundance Hot Tub

IMPORTANT: Because of the combined weight of the spa, water and users, it is extremely important that the base upon which the spa rests be smooth, flat, level and capable of uniformly supporting this weight, without shifting or settling, for the entire time the spa is in place. If the spa is placed on a surface which does not meet these requirements, damage to the skirt and/or the spa shell may result. Damage caused by improper support is not covered under warranty. It is the responsibility of the spa owner to assure the integrity of the support over time. We recommend a poured, reinforced concrete slab with a minimum thickness of 4 inches (10 cm). Wood decking is also acceptable provided it is constructed so that it meets the requirements outlined above.



WARNING: For spas that are to rest on balconies, roofs or other platforms not specifically tied into main structural support, consult a professional Structural Engineer with experience in this type of application.

The spa must be installed in such a manner as to provide drainage away from it. Placing the spa in a depression without provisions for proper drainage could allow rain, overflow and other casual water to flood the equipment and create a wet condition in which it would sit in. For spas which will be recessed into a floor or deck, install so as to permit access to the equipment, either from above or below, for servicing. Make certain that there are no obstructions which would prevent removal of all side cabinet panels and access to components, especially on the side with the equipment bay doors.



CAUTION: If the spa is indoors or located in an enclosed area, proper ventilation should be discussed with an Engineer or authority competent enough to understand the necessary provisions needed to vent moist or heated air and air associated with chemical odors outdoors. When the spa is in use considerable amounts of moisture will escape potentially causing mold and mildew. This can cause health risk. Over time, this can damage certain surfaces, surroundings, and equipment.

4.1 Outdoor Location

In selecting the ideal outdoor location for your hot tub, we suggest that you take into consideration the following:

- The proximity to changing area and shelter (especially in regions subject to cold weather).
- The pathway to and from your hot tub (this should be free of debris so that dirt and leaves are not easily tracked into the hot tub).
- The closeness to trees and shrubbery (remember that leaves and birds could create extra work in keeping the hot tub clean).
- A sheltered environment (less wind and weather exposure can result in lowered operation and maintenance costs).
- The overall enhancement of your environment. It is preferable not to place the hot tub under an unguttered roof overhang since run-off water will shorten the life expectancy of the hot tub cover.
- For spas that are to rest on balconies, roofs or other platforms not specifically tied into main structural support, consult a professional Structural Engineer with experience in this type of application.
- In the unlikely event that you should ever need to access or gain entry to any portion of the spa for servicing, it is highly recommended that you plan your outdoor installation to provide full access to the entire spa. Please take this into consideration when placing the spa in a deck or enclosed by a surrounding.
- Consider locating your spa away from any reflective surface or glass to prevent any damage to the synthetic skirt.
- Do not shim the spa. To ensure proper support the spa must sit flat on the intended foundation.

4.2 Indoor Location

For indoor installations many factors need to be considered before installing a spa indoors:



WARNING: In addition to maintenance of filters and water chemistry, proper ventilation is recommended to reduce the risk of contracting a waterborne illness (e.g. an infection, bacteria or virus) and/or respiratory ailments that could be present in the air or water. Consult a licensed architect or building contractor to determine your specific needs if installing your hot tub indoors.

- PROPER FOUNDATION: <u>Consult a Structural Engineer when considering a foundation that will adequately support the spa the entire time it is in place.</u> Proper support is critical especially if the spa is to rest on a second story or higher. For spas that are to rest on balconies, roofs or other platforms not specifically tied into the main structural support, you should consult a professional Structural Engineer with experience in this type of application.
- PROPER DRAINAGE: It is extremely important to have in place measures to sufficiently handle excessive water spillage. Be sure the flooring in which the spa rests on has adequate drainage and can handle draining of the entire contents of the spa. Be sure to make provisions for ceilings or any other structures that may be below the spas installation. Areas around your spa can become wet or moist so all flooring and subsequent furniture, walls and adjacent structures should be able to withstand or resist water and moisture.
- PROPER VENTILATION: Proper ventilation should be discussed with an Engineer or authority competent enough to understand the necessary provisions needed to vent moist or heated air and air associated with chemical odors outdoors. When the spa is in use considerable amounts of moisture will escape potentially causing mold and mildew, over time this can damage certain surfaces and or surroundings.
- SUFFICIENT ACCESS: In the unlikely event that you should ever need to access or gain entry to any portion of the spa for servicing, it is highly recommended that you plan your indoor installation to provide full access to the entire spa.
- WARRANTY: Damage caused by not following these guidelines or any improper installation not in accordance with local codes or authorities is not covered under the spas warranty. Please consult your local state or city building ordinances.
- DO NOT SHIM THE SPA. To ensure proper support the spa must sit flat on the intended foundation.

5.0 General Electrical Safety Instructions

Your new Sundance® hot tub is equipped with the "state-of-the-art" equipment system. It contains the most advanced safety and self-protective equipment in the industry.

Nonetheless, this hot tub must be installed properly to ensure dependable usage. Please contact your local Sundance Spas dealer or local building department should you have any questions regarding your installation.

Proper grounding is extremely important. Sundance hot tubs are equipped with a current collector system. A pressure wire connector is provided on the surface of the control box, located inside the equipment door (Figure C, page 15) to permit connection of a bonding wire between this point and any ground metal equipment, metal water pipe or conduit within 5 feet (1.5m) of the hot tub, or copper clad grounding rod buried within 5 feet (1.5m) of the hot tub. Bonding wire must be at least No. 8 AWG (8.4 mm²) solid copper wire. This is a most important safety assurance feature.

Before installing your hot tub, check with your local government/electrical authority to ensure installation conforms to local country/area state codes.

6.0 Electrical Installation Instructions (240V Service) IMPORTANT NOTICE: The electrical wiring of this hot tub must meet the requirements of the National Electrical Code (NEC) and/or any applicable state, local or country codes. The electrical circuit must be installed by a qualified electrician and approved by a local building/electrical inspection authority in your state or country.



1. **DANGER:** TO DECREASE THE RISK OF SHOCK, PRODUCT DAMAGE OR ELECTRICAL FIRE.

This hot tub must be permanently connected (hard-wired) to the power supply. No plug-in connections or extension cords are to be used in conjunction with the operation of this hot tub. Supplying power to the hot tub which is not in accordance with these instructions will void both the independent testing agency listing and the manufacturer's warranty.

- 2. The power supplied to this hot tub must be a dedicated circuit with no other appliances or lights sharing the power provided by the circuit.
- 3. To determine the current, voltage and wire size required, refer to Section 7.0 (page 16) for your specific hot tub model.
- Wire size must be appropriate per NEC and/or local/country codes.
- The spa controller's terminal block will accept a maximum wire size of 6 AWG.
- 4. The electrical supply for this product must include a suitably rated switch or circuit breaker to open all ungrounded supply conductors to comply with Section 422-20 of the National Electrical Code, ANSI/ NFPA 70. The disconnecting means must be readily accessible and visible to the hot tub's occupant but installed at least 5 feet (1.5m) from the hot tub.
- The electrical circuit supplied for the hot tub must include a suitable ground fault circuit interrupter (GFCI) as required by NEC Article 680-42.
- 6. To gain access to the spa's power terminal block:
- For Maxxus and Aspen Cabinet remove the screws securing the center cabinet panel on the side of the hot tub under the controls. Then remove the control box door screws and door.
- For 880 SunStrong® Cabinet Press the retractable push buttons
 to release the panel door from the spa frame, Figure A. Slowly and
 gently tilt the panel forward and then lift up to remove. Place the
 panel in a safe location to prevent from damaging it. Reference page
 71, for instructions. Then remove the door screws on the control
 box.
- For 880 SunSide™ Cabinet Remove both corner panels. Grab one
 of the corner panels, from the bottom, and gently pull the cabinet
 forward to unsnap it from the holding clip. Then slide it down to
 remove. Now remove the center cabinet by grabbing the bottom of
 the panel and lifting it up to release from the top mounting bracket.
 Then slightly tilt and pull down on the panel to remove.Place the

- panel is a safe location to prevent from damaging it. Then remove the door screws on the control box. Reference page 71, for instructions. Then remove the control box door screws and door (Figure C, page 15).
- 7. Select the power supply entrance you want to use (Figures A-B, pages 14-15) and remove the short cabinet panel from the front of the hot tub, then feed cable through the large opening provided on the bottom of the control box.
- Connect wires, color to color, on terminal blocks TB1 (Figure D). TIGHTEN SECURELY! All wires must be hooked up securely or damage could result.
- 9. Install control box door and reinstall the cabinet panel(s).



IMPORTANT NOTICE: Remove the shipping bolts and spacers from the circulation pump prior to operation. Failure to do so may result in loud pump noise. Store the bolts and spacers in a safe location. Reinstall them if you move, tilt or ship the hot tub.


Figure A (Maxxus/Aspen Equipment Area)

Note: Equipment location (such as pumps, CLEAR**RAY**® system, drain, heater etc.) varies by model.

- 9. Pump Drain Plug(s)
- 10. Filter/Circulation Pump
- 11. CLEAR**RAY**® (Ultraviolet) Water Purification System
- 12. Control Panel
- Quick Drain
- 14. SmartTub™ System (Optional)
- Bridge (for optional SmartTub System)
- 15. BLUEWAVE® 2.0 Wireless Audio System (Optional)

- 1. Control Box
- 2. Power Supply Entrance(s)
- 3. Jets Pump
- 4. Jets Pump
- 5. Jets Pump
- 6. Blower
- 7. Heater
- 8. Hot Tub Drain (Removable External Drain Cap)


Figure B (Equipment Area for All Models Except Maxxus/Aspen)



Note: Equipment location (such as pumps, CLEAR**RAY**® system, drain, heater etc.) varies by model.

- 9. Filter/Circulation Pump
- 10. CLEAR**RAY**® (Ultraviolet)
 Purification System
- 11. Control Panel
- 12. Quick Drain
- 13. SunSmart™ System (Optional)
- 14. Bridge (for optional SunSmart System)
- 15. BLUEWAVE® 2.0 Wireless Audio System (Optional)

- 1. Control Box
- 2. Power Supply Entrance(s)
- 3. Jets Pump
- 4. Heater
- Hot Tub Drain (Removable External Drain Cap SunStrong® Cabinet only)
- 6. Air Blower
- 7. Pump Drain Plug(s)
- 8. Jets Pump



7.0 Power Requirements

Sundance® hot tubs are designed to provide optimum performance and flexibility of use when connected to their maximum electrical service. However, they are shipped factory configured for their most common preferred electrical connection. If you prefer, a qualified technician



can perform a minor circuit board modification that allows the hot tub to operate on a different electrical service.

North American 60 Hz			
Voltage	240 VAC	240 VAC	240 VAC
Max. Current Draw: 1-Pump System 2-Pump System 3-Pump System	28A 28A N/A	39A 39A 39A	N/A 48A 48A
Frequency:	60 Hz	60 Hz	60 Hz
Number of Wires:	3	3	3
Circuit Breaker (2-Pole):	40A*	50A**	60A***

- In the 40A configuration, the heater <u>will not operate</u> while any jets pump is running. <u>Not recommended for the Maxxus and Aspen.</u>
- ** In the 50A configuration, the heater <u>will operate</u> when one jets pump is running, but <u>will not operate</u> while two jets pumps are running. <u>This is the factory default setting for 1-pump and 2-pump systems.</u>
- *** In the 60A configuration, the heater <u>will operate</u> while two jets pumps are running, but <u>will not operate</u> if three jets pumps are running.

8.0 Hot Tub Fill Up Procedure

For best results, read each step in its entirety before proceeding with that step. Make sure all drains are closed prior to filling spa, page 14.

1. Prepare The Hot Tub For Filling

- Clear all debris from the hot tub. (Although the hot tub shell has been polished at the factory, you may want to treat it with a specially formulated hot tub cleaner.) Consult your dealer for additional information prior to filling hot tub.
- If using the primary filter inlet to fill, remove filter cover, then remove filter cartridge as outlined in Section 13.1.

IMPORTANT: In most cases, filling the spa by placing the hose in the footwell will not create an airlock, page 87. If you experience an airlock we recommend filling by placing the end of your garden hose into the primary filter inlet, page 69.

2. Fill Hot Tub

 Place the end of your garden hose into the one of the following primary filter inlet or footwell.

CAUTION: TO DECREASE BUILD UP ON COMPONENTS AND MINIMIZE ACRYLIC DAMAGE.

Never fill with water from a water softener. If your water is extremely "hard," it is preferable to fill half-way with hard water and the rest of the way with softened water. Water that is too soft can be corrosive to metal components.

• VARNING: TO DECREASE RISK OF INFECTION OR DISEASE.

Fill hot tub with clean tap water from garden hose, to reduce risk of contracting a waterborne illness (e.g. an infection, bacteria or virus) and/or respiratory ailments. Fill until water covers all jets but does not touch the bottom of the lowest headrest. (DO NOT OVERFILL!)

3. Turn On Power

Turn on power to hot tub at the home's circuit breaker to start boot up sequence. The heater and filter/circulation pump will automatically activate.

4. Activate Jets Pumps

Turn on all jet(s) pumps and blower to ensure proper mixing when adding start up chemical in step 5.



5. Add Start-Up Chemicals

Add the hot tub water chemicals as recommended by your Sundance Spas dealer. See Section titled "Water Quality Maintenance" (page 77) for general guidance.



WARNING: RISK OF POISONING OR DEATH.

Never leave chemicals opened and accessible to anyone. Use chemicals according to the vendors instructions. Always store chemicals in a safe and/or locked location. Keep away from and out of reach of children.

6. Establish A Stable Sanitizer Reading

Establish a stable sanitizer reading no less than 1.0 ppm free chlorine or 2.0 ppm bromine. To ensure healthy water conditions, always maintain a constant sanitizer reading within the levels recommended on the inside cover of this manual.

7. Set Hot Tub To Heat



To warm hot tub water to a comfortable temperature, follow these steps:

- The LCD display on the control panel displays the actual temperature of the hot tub water. Press either the COOLER (♥) or WARMER (♠) button once to display the "set" temperature for 5 seconds. If you want the water to heat to a different temperature, simply press COOLER or WARMER within 5 seconds. The set temperature increases or decreases by 1°F (0.5°C) each time either button is pressed.
- The heater will turn off when the temperature corresponding to the thermostat setting is achieved.

Important Heater Details:

- The maximum temperature for which the hot tub can be set is 104°F (40°C) and the minimum is 65°F (18.33°C).
- For hot tubs powered with a 40 amp service, turn off jets pump #1 and jets pump #2 to operate heater.
- Setting the thermostat at maximum will not accelerate the heating process. This will only result in a higher ultimate temperature.
- The heater operates until the water reaches the programmed "set temperature," then turns off. The heater will reactivate after the water cools to approximately 2°F (1°C) below the "set temperature."

8. Place Cover On Hot Tub

- Keeping the insulating cover in place anytime the hot tub is not in use will reduce the time required for heating, thereby minimizing operating costs.
- The time required for initial heat-up will vary depending on the starting water temperature.



DANGER: RISK OF PERSONAL INJURY.

Check water temperature carefully before entering hot tub! Excessive water temperature can cause burns, welts and body temperature to rise, hyperthermia (over-heating).

Decontamination Procedure (Steps 9-15)

Steps 9-15 below are only required when sanitizer levels are unstable after performing steps 1-6 above. Disregard steps 9-15 below if sanitizer levels remain stable after performing steps 1-6 above (refer to the inside cover of the manual).

Note: The "decontamination procedure" steps 9-15 should also be used after the hot tub has been "Winterized" (Section 13.8) or has been sitting without power for an extended period.

 Add 2.5 ounces (71 g.) of sodium dichlor for every 100 gallons (378 L.) of water. Refer to the table (below) for approximate water fill capacity by model.



CAUTION: RISK OF PERSONAL INJURY OR SPA DAMAGE! Never add chlorine tablets (trichlor) or acid to your hot tub for any reason! These chemicals may damage components within your hot tub, burn or irritate your skin, create a rash, and void the manufacturer warranty for your spa.

Water Fill Volume

	Average	
Model	Fill Volume*	Dichlor
Altamar	390 Gal (1,476 L)	10.0 oz
Aspen	563 Gal (2,131 L)	14.0 oz
	335 Gal (1,268 L)	
Cameo	370 Gal (1,401 L)	9.0 oz
Capri	230 Gal (871 L)	6.0 oz
Marin	320 Gal (1,211 L)	8.0 oz
Optima	410 Gal (1,552 L)	10.25 oz
Maxxus	570 Gal (2,158 L)	14.25 oz

^{*}Use average fill volume for chemical maintenance

10. Leave hot tub cover open during this step to allow excessive chemical vapors to exit hot tub, protecting pillows and plastic knobs from chemical attack. If hot tub is indoors, open doors and windows for proper ventilation. Turn on all hot tub jets pumps for one hour, open all air controls, turn on the blower, and place all massage selector knob(s) in their center "combo" position as shown (right).

Note: You will need to press the jets pump button(s) and blower button every 20 minutes since these functions have an automatic 20 minute time-out function that turns them off.



WARNING: RISK OF PERSONAL INJURY!

- To decrease the risk of injury, drowning or entrapment, never leave your hot tub unattended for any reason while the cover is open and accessible, especially to small children and animals!
- Precautions should be taken to minimize your exposure to chemical vapors (that could cause lung, brain, or skin damage).
- 11. Turn off power to the hot tub at the circuit breaker, then drain tub as outlined in Section 13.3 (page 73).
- 12. Refill hot tub with clean tap water from garden hose until water covers all jets but does not touch the bottom of the lowest headrest. (DO NOT OVERFILL!)

CAUTION: TO DECREASE BUILD UP ON COMPONENTS AND MINIMIZE ACRYLIC DAMAGE.

Never fill with water from a water softener. If your water is extremely "hard," it is preferable to fill half-way with hard water and the rest of the way with softened water. Water that is too soft can be corrosive to metal components.

- 13. Consult your authorized Sundance Spas dealer for chemical recommendations, then add chemicals to hot tub water to achieve a constant sanitizer reading within the levels recommended on the inside cover of this manual.
- 14. Turn on all jet pumps and the blower when adding chemicals to ensure proper mixing and leave your hot tub cover open until the sanitizer level becomes stable to protect pillows and plastic knobs from chemical attack. Refer to the inside cover of the manual.



WARNING: RISK OF PERSONAL INJURY.

- To decrease the risk of injury, entrapment or drowning, never leave your hot tub unattended for any reason, especially if while the cover is open and accessible to small children and animals!
- To decrease the risk of contracting a waterborne illness (e.g. an infection, bacteria or virus) and/or respiratory ailments, maintain water chemistry within 6 step parameters. If you or other bathers experience such a condition, discontinue use and seek immediate medical attention.


15. Establish a sanitizer reading no less than 1.0 ppm free chlorine or 2.0 ppm bromine, then allow the hot tub to set undisturbed for 8 hours. Retest water after 8 hours to determine if sanitizer levels are stable. If sanitizer levels are stable, your hot tub is ready for use. To ensure healthy water conditions, always maintain a constant sanitizer reading within the levels recommended on the inside cover of this manual. If sanitizer levels are not stable at this time, it will be necessary to repeat this procedure in its entirety (steps 1-15) until stable sanitizer readings are achieved.

IMPORTANT: If the CLEAR**RAY**® water purification system is removed from the hot tub or is not operating efficiently follow the "without CLEAR**RAY**®" water chemistry parameters. Such parameters are defined by the Association of Pool and Spa Professionals.

16. After adequate sanitizer levels are achieved, close all spa air controls by rotating them counterclockwise to maximize heat retention when spa is not in use.

Hot Tub Features 9.0

9.1 Maxxus™ Hot Tub Features



- Main Control Panel
- 2. Handrails with LED Light (2 ea.)
- 3. Lights (2 ea.)
- 4. Pillows (4 ea.)
- Fluidix Nex Jets (8 ea.)
- Fluidix Intelli-Jets (2 ea.) 6.
- 7. Air Controls with LED Light (8 ea.)
- 8. Whirlpool Jets (2 ea.)
- **Gravity Drain**
- 10. Massage Selectors (2 ea.)
- 11. Air Injectors (6 ea.)
- 12. Suction Covers (6 ea.; one is not shown)
- 13. Accu-Pressure Jets (14 ea.)
- 14. Weir Gate/Skimmer
- 15. Filter Lid (The filter cartridge and suction fitting/filter are located under the filter lid. The suction fitting filter


- requires periodic cleaning for optimum performance)
- 16. Waterfall Control Valve
- 17. Waterfall Filtration Return
- 18. Fluidix ST Jets (12 ea.)
- 19. Waterfalls (2 ea.)
- 20. Pulsator Jets (6 ea.)
- 21. Optional BLUEWAVE® 2.0 Wireless Spa Stereo (behind cabinet)
- 22. Optional Audio System Speakers (4 ea.)
- 23. Sunscents™ Dispenser24. Vortex Jets (7 ea.)
- 25. Integrated cupholders (4 ea.)
- 26. Fluidix Reflex Jets (6 ea.)
- 27. Focus-Relief Jets (8 ea.)

Spa features subject to change without notice.

9.2 Maxxus Massage/Waterfall Selector Diagram

Massage Selector Operation

Rotate Massage Selectors 1 and 2 to divert water between designated jet groups.



Massage Selectors (1-2)

- Massage Selector #1 controls pump #2.
- Massage Selector #2 controls pump #3.

Waterfall Selector (3)

Waterfall Selector #3 controls circulation pump output to waterfall.

Continuously Powered Jets


• Jets #4 are always on when jets pump #1 is running.

Spa operation subject to change without notice.


9.3 Maxxus Air Controls Diagram

Air Control Operation

Rotate Air Controls 1-8 to add air to designated jet groups. Turn the Blower on to add air to jets group 9.



9.4 Aspen® Hot Tub Features



- 1. Main Control Panel
- 2. Handrails with LED Light (2 ea.)
- Lights (2 ea.) 3.
- Pillows (4 ea.) 4.
- Fluidix Nex Jets (8 ea.) 5.
- 6. Fluidix Intelli-Jets (6 ea.)
- Air Controls with LED Light (8 ea.) 7.
- 8. Whirlpool Jets (2 ea.)
- Gravity Drain
- 10. Massage Selectors (2 ea.)
- 11. Air Injectors (14 ea.)
- 12. Suction Covers (6 ea.; one is not shown)
- 13. Accu-Pressure Jets (18 ea.)
- 14. Weir Gate/Skimmer
- 15. Filter Lid (The filter cartridge and suction fitting/filter are located under


- the filter lid. The suction fitting filter requires periodic cleaning for optimum performance)
- 16. Waterfall Control Valve
- 17. Waterfall Filtration Return
- 18. Fluidix ST Jets (12 ea.)19. Waterfalls (2 ea.)
- 20. Pulsator Jets (4 ea.)
- 21. Optional BLUEWAVE® 2.0 Wireless Spa Stereo (behind cabinet)
- 22. Optional Audio System Speakers (4 ea.)
- 23. Sunscents™ Dispenser
- 24. Vortex Jets (2 ea.)
- 25. Integrated cupholders (4 ea.)
- 26. Fluidix Reflex Jets (14 ea.)

Spa features subject to change without notice.

9.5 Aspen Massage/Waterfall Selector Diagram

Massage Selector Operation

Rotate Massage Selectors 1 and 2 to divert water between designated jet groups.



Massage Selectors (1-2)

- Massage Selector #1 controls pump #1.
- Massage Selector #2 controls pump #2.

Waterfall Selector (3)

Waterfall Selector #3 controls circulation pump output to waterfall.

Continuously Powered Jets


• Jets #4 are always on when jets pump #3 is running.

Spa operation subject to change without notice.


9.6 Aspen Air Controls Diagram

Air Control Operation

Rotate Air Controls 1-8 to add air to designated jet groups.



9.7 Optima® Hot Tub Features



- 1. Main Control Panel
- 2. Handrails with LED Light (2 ea.)
- 3. Light
- 4. Pillows (4 ea.)
- 5. Fluidix Nex (4 ea.)
- 6. Fluidix Intelli-Jets (5 ea.)
- 7. Air Controls w/LED Light (5 ea.)
- 8. Whirlpool Jets (1 ea.)
- 9. Gravity Drain
- 10. Massage Selectors (2 ea.)
- 11. Air Injectors (14 ea.)
- 12. Suction Covers (4 ea.; one is not shown)
- 13. Accu-Pressure Jets (12 ea.)
- 14. Weir Gate/Skimmer
- Filter Lid (The filter cartridge and suction fitting/filter are located under the filter lid. The


- suction fitting filter requires periodic cleaning for optimum performance)
- 16. Waterfall Control Valve
- 17. Waterfall Filtration Return
- 18. Fluidix ST Jets (16 ea.)
- 19. Waterfall
- Optional BLUEWAVE® 2.0
 Wireless Spa Stereo (behind cabinet)
- 21. Optional Audio System Speakers (4 ea.)
- 22. Sunscents Dispenser
- 23. Vortex Jets (7 ea.)
- 24. Integrated Cupholders (3 ea.)
- 25. Pulsator Jets (2 ea.)

Spa features subject to change without notice.

9.8 Optima Massage/Waterfall Selector Diagram

Massage Selector Operation

Rotate Massage Selectors 1 and 2 to divert water between designated jet groups.



Massage Selectors (1-2)

- Massage Selector #1 controls pump #1.
- Massage Selector #2 controls pump #2.

Waterfall Selector (3)

Waterfall Selector #3 controls circulation pump output to waterfall.

Continuously Powered Jets


- Jets #4 are always on when jets pump #1 is running.
- Jets #5 are always on when jets pump #2 is running.

Spa operation subject to change without notice.


9.9 Optima Air Controls Diagram

Air Control Operation

Rotate Air Controls 1-5 to add air to designated jet groups.



9.10 Cameo® Hot Tub Features



- 1. Control Panel
- 2. Handrails with LED Light (2 ea.)
- 3. Light
- 4. Pillows (3 ea.)
- 5. Fluidix Nex Jets (6 ea.)
- 6. Fluidix Intelli-Jets (2 ea.)
- 7. Air Controls w/LED Light (5 ea.)
- 8. Whirlpool Jets (4 ea.)
- 9. Gravity Drain
- 10. Massage Selectors (2 ea.)
- 11. Air Injectors (6 ea.)
- 12. Suction Covers (4 ea.; one is not shown)
- 13. Accu-Pressure Jets (6 ea.)
- 14. Weir Gate/Skimmer
- Filter Lid (The filter cartridge and suction fitting/filter are located under the filter lid. The


- suction fitting filter requires periodic cleaning for optimum performance)
- 16. Waterfall Control Valve
- 17. Waterfall Filtration Return
- 18. Fluidix ST Jets (12 ea.)
- 19. Waterfall
- Optional BLUEWAVE® 2.0
 Wireless Spa Stereo (behind cabinet)
- 21. Optional Audio System Speakers (4 ea.)
- 22. Sunscents Dispenser
- 23. Vortex Jets (6 ea.)
- 24. Pulsator Jets (4 ea.)
- 25. Integrated Cupholders (3 ea.)
- 26. Fluidix Reflex Jets (6 ea.)
- 27. Focus-Relief Jets (8 ea.)

Spa features subject to change without notice.

9.11 Cameo Massage/Waterfall Selector Diagram

Massage Selector Operation

Rotate Massage Selectors 1 and 2 to divert water between designated jet groups.



Massage Selectors (1-2)

- Massage Selector #1 controls pump #2.
- Massage Selector #2 controls pump #1.


Waterfall Selector (3)

• Waterfall Selector #3 controls circulation pump output to waterfall.


9.12 Cameo Air Controls Diagram

Air Control Operation

Rotate Air Controls 1-5 to add air to designated jet groups. Turn the Blower on to add air to jets group 6.



9.13 **Altamar® Hot Tub Features**



- Main Control Panel 1.
- Handrail with LED Light 2.
- 3. Light
- 4.
- Pillows (3 ea.) Fluidix Nex (4 ea.) 5.
- 6. Fluidix Intelli-Jets (6 ea.)
- 7. Air Controls w/LED Light (5 ea.)
- Whirlpool Jets (3 ea.)
- Gravity Drain
- 10. Massage Selectors
- 11. Air Injectors (8 ea.)
- 12. Suction Covers (4 ea.; one is not shown)
- 13. Pulsator Jets (2 ea.)
- 14. Weir Gate/Skimmer
- 15. Filter Lid (The filter cartridge and suction fitting/filter are

located under the filter lid. The suction fitting filter requires periodic cleaning for optimum performance)


- 16. Waterfall Control Valve
- 17. Waterfall Filtration Return
- 18. Fluidix ST Jets (12 ea.)
- 19. Waterfall
- 20. Optional BLUEWAVE® 2.0 Wireless Spa Stereo (behind cabinet)
- 21. Optional Audio System Speakers (4 ea.)
- 22. Sunscents Dispenser
- 23. Vortex Jets (2 ea.)
- 24. Integrated Cupholders (2 ea.)
- 25. Fluidix Reflex (6 ea.) 26. Focus-Relief Jets (6 ea.)

Spa features subject to change without notice.

9.14 Altamar Massage/Waterfall Selector Diagram

Massage Selector Operation

Rotate Massage Selector 1 to divert water between designated jet groups.



Massage Selectors (1)

Massage Selector #1 controls pump #2.

Waterfall Selector (2)

· Waterfall Selector #2 controls circulation pump output to waterfall.

Continuously Powered Jets


• Jets #3 are always on when jets pump #1 is running.

Spa operation subject to change without notice.


9.15 Altamar Air Controls Diagram

Air Control Operation

Rotate Air Controls 1-5 to add air to designated jet groups. Turn the Blower on to add air to jets group 6.



9.16 Marin® Hot Tub Features



- 1. Main Control Panel
- 2. Air Controls w/LED Light (4 ea.)
- 3. Light
- 4. Pillows (4 ea.)
- 5. Fluidix Nex (4 ea.)
- 6. Fluidix Intelli-Jets (2 ea.)
- 7. Fluidix Reflex Jets (6 ea.)
- 8. Gravity Drain
- 9. Waterfall Filtration Return
- 10. Massage Selector
- 11. Air Injectors (4 ea.)
- 12. Suction Covers (4 ea.; one is not shown)
- 13. Accu-Pressure Jets (2 ea.)
- 14. Weir Gate/Skimmer
- 15. MicroClean® Plus Versatile Filter Lid (The filter cartridge and


- suction fitting/filter are located under the lid. The suction fitting filter requires periodic cleaning for optimum performance)
- 16. Waterfall Control Valve
- 17. Waterfall
- 18. Fluidix ST Jets (12 ea.)
- 19. Vortex Jets (7 ea.)
- 20. Pulsator Jets (2 ea.)
- 21. Focus-Relief Jets (10 ea.)
- 22. Sunscents Dispenser
- 23. Integrated Cupholders (2 ea.)
- 24. Optional BLUEWAVE® 2.0
 Wireless Spa Stereo (behind cabinet)
- 25. Optional Audio System Speakers (4 ea.)

Spa features subject to change without notice.

9.17 Marin Massage/Waterfall Selector Diagram

Massage Selector Operation

Rotate Massage Selector 1 to divert water between designated jet groups.



Massage Selectors (1)

Massage Selector #1 controls pump #2.

Waterfall Selector (2)

Waterfall Selector #2 controls circulation pump output to waterfall.

Continuously Powered Jets


• Jets #3 are always on when jets pump #1 is running.

Spa operation subject to change without notice.


9.18 Marin Air Controls Diagram

Air Control Operation

Rotate Air Controls 1-4 to add air to designated jet groups. Turn the Blower on to add air to jets group 5.



9.19 Cambria™ Hot Tub Features



- 1. Main Control Panel
- 2. Air Controls w/LED Light (4 ea.)
- 3. Light
- 4. Pillows (3 ea.)
- 5. Fluidix Nex (6 ea.)
- 6. Fluidix Intelli-Jets (2 ea.)
- 7. Gravity Drain
- 8. Waterfall Filtration Return
- 9. Massage Selector
- 10. Air Injectors (6 ea.)
- 11. Suction Covers (4 ea.; one is not shown)
- 12. Accu-Pressure Jets (2 ea.)
- 13. Weir Gate/Skimmer
- MicroClean® Plus Versatile Filter Lid (The filter cartridge and suction fitting/filter are located under the lid. The suction fitting filter


- requires periodic cleaning for optimum performance)
- 15. Waterfall Control Valve
- 16. Waterfall
- 17. Fluidix ST Jets (16 ea.)
- 18. Vortex Jets (8 ea.)
- 19. Pulsator Jets (4 ea.)
- 20. Focus-Relief Jets (8 ea.)
- 21. Sunscents Dispenser
- 22. Integrated Cupholders (3 ea.)
- Optional BLUEWAVE® 2.0
 Wireless Spa Stereo (behind cabinet)
- Optional BLUEWAVE® 2.0
 Wireless Spa Stereo (behind cabinet)
- 25. Grab bar

Spa features subject to change without notice.

9.20 Cambria Massage/Waterfall Selector Diagram

Massage Selector Operation

Rotate Massage Selector 1 to divert water between designated jet groups.



Massage Selectors (1)

Massage Selector #1 controls pump #1.

Waterfall Selector (2)

Waterfall Selector #2 controls circulation pump output to waterfall.

Continuously Powered Jets


Jets #3 are always on when jets pump #2 is running.

Spa operation subject to change without notice.


9.21 Cambria Air Controls Diagram

Air Control Operation

Rotate Air Controls 1-4 to add air to designated jet groups. Turn the Blower on to add air to jets group 5.



9.22 Capri® Hot Tub Features




- Control Panel
- 2. Integrated Handrail
- 3. Gravity Drain
- 4. Pillows (3 ea.)
- 5. Fluidix Nex Jets (2 ea.)
- 6. Fluidix ST Jets (10 ea.)
- 7. Air Controls (2 ea.)
- 8. Waterfall Control Valve (1 ea.)
- 9. Light
- 10. Massage Selectors (1 ea.)
- 11. Air Injectors (10 ea.)
- 12. Fluidix Reflex Jets (6 ea.)
- 13. Pulsator Jets (2 ea.)
- 14. Fluidix Intelli-Jets (2 ea.)
- 15. Vortex Jet (1 ea.)

- Filter Lid (The filter cartridge and suction fitting/filter are located under the filter lid. The suction fitting requires periodic cleaning for optimum performance)
- 17. Weir Gate/Skimmer
- 18. Waterfall
- 19. SunScents Dispenser
- 20. Footwell Suction Cover (2 ea. one is not shown)
- 21. Focus-Relief Jets (4 ea.)
- 22. Accu-Pressure Jets (4 ea.)
- Optional BLUEWAVE® 2.0 Wireless Spa Stereo (behind cabinet)
- 24. Optional Audio System Speakers (4 ea.)

9.23 Capri Massage/Waterfall Selector Diagram

Massage Selector Operation

Rotate Massage Selector 1 to divert water between designated jet groups.



Massage Selectors (1)

Massage Selector #1 controls pump #1.


Waterfall Selector (2)

• Waterfall Selector #2 controls circulation pump output to waterfall.

9.24 Capri Air Controls Diagram

Air Control Operation

Rotate Air Controls 1-2 to add air to designated jet groups. Turn the Blower on to add air to jets group 3.



10.0 Registration and Start-up

10.1 Start-up Sequence

When power is first applied, the iTouch™ control panel will display a welcome message and the current software revisions, Figures 10.1a. Then the spa will begin a blow out cycle, Section 12.5, page 61.

Note: The start up menu will time out after approximately 3 seconds.





Figure 10.1a

10.2 Register Your New Spa

Registering your spa is important in order to validate your warranty. To register you will need to have the spa serial number, Figure 10.2a, then you will need to register online at www.SundanceSpas.com.




Figure 10.2a

Follow these steps to register your spa.

- 1. Using your home computer or other device, connect to the internet.
- 2. Go to www.SundanceSpas.com website to register your spa.
- 3. Click Owner Resources
- 4. Click Warranty Registration
- 5. Enter your serial number.
- 6. Click **Next** to continue to complete your registration.

10.3 iTouch™ Control Panel Main Menu

The new iTouch™ system makes operating your spa a breeze. The Home Menu, Figure 10.3a, provides access to spa functions and programming. You can navigate through the menus and sub-menus with ease. Simply touch the icons on the LCD display to begin operating your new Sundance spa. Operation is made easy by the interactive control panel.

Note: If there is no activity for 30 minutes, the LCD display, will time-out into a sleep mode. To reactivate the display, just tap the display screen.

A. Home Menu Control Buttons



Figure 10.3a



- **Temperature Control:** Allows you to adjust the set temperature of the spa:
 - Increase the temperature by tapping in 1°F (0.5°C) increments.
 - Decrease the temperature by tapping ▼ in 1°F (0.5°C) increments.

Note: The temperature range for the spa is 65 to 104°F (18.33 to 40°C). To activate the **Extended Temperature feature** that allows the spa to reach 106°F (41°C), see page 86.



= Jet Button: Tap to access the menu to operate the jets pumps, page 45.



Light Button: Tap to access the menu to operate the lighting options, page 49.



 CLEARRAY Button: Tap to activate the CLEARRAY on demand feature, page 53.



Settings Button: Tap to access the programming and setting menus, page 57.



Music Button: Tap to access the menu to operate the audio system and settings, page 50.

Note: If the spa does not have the stereo option, there will not be a button on the control panel.



Error Indicator Icon: Displays when there is an error message that needs to be addressed. The icon will also appear at the Home Menu as a reminder, page 83. Tap to view the condition that requires attention.



= Invert Button: Tap to invert the display image.



= Heater ON icon: Will display when the heater is on.



Lock Button: Displays when one of the lock modes is enabled, page 65.



Wi-Fi icon: Will display when the Wi-Fi feature is on, page 64 (50Hz Models only).

12:42 PM = **Time Indicator:** The time will always be shown when the Home Menu is displayed. The appearance will vary depending on whether the clock is set to a 12-Hour or 24-Hour configuration, page 66. The default setting is 12-Hour.

Note: The time does NOT automatically adjust for daylight saving time. The time must be manually adjusted.

11.0 Operating Instructions

Your Sundance[®] Spas hot tub has a touch-sensitive control panel, massage selector valves and air control knobs located on the top rim of the hot tub (Sections 9.1-9.22, pages 22-40). These controls let you operate many of the special functions of your Sundance hot tub. By familiarizing yourself with the following information, you will be able to gain the full benefits afforded by the various functions of your hot tub.

11.1 Activating the Jets Pumps and Blower

From the Home Menu, (Figure 11.1a), tap to enter the Submenu. The panel will display the Jets Pump Submenu (Figure 11.1b).

Note: Once you enter the Jets Pump Submenu, all the pumps will activate. You can turn off the jets pump by tapping the jets pump button.



Figure 11.1a



Figure 11.1b

- 1 = Jets Pump 1 Button
- = Jets Pump 2 Button (If applicable)
- 3 = Jets Pump 3 Button (If applicable)
- = Blower Button
- = Home Button: Tap to go back to the Home Menu.
- A. Jets Pumps
- 1. Tap the Jets 1 button to turn the pump on and off.
- Tap the Jets 2 button to turn the pump on and off.
- 3. Tap the Jets 3 button to turn the pump on and off.

Note: Anytime a pump has been manually turned on, it will automatically turn off after approximately 20 minutes. If at this time you desire more jet operation you may simply turn the pump(s) back on.

B. Air Injection

Tap to turn the blower on and off. The air blower forces air through the injectors and Focus-Relief Jets. The blower automatically turns off after 20 minutes.

11.2 Lights Menu

From the Home Menu, (Figure 11.2a), tap to enter the Light submenus. The LCD screen will display the Light Submenu (Figure 11.2b). From this menu you can control the hot tub lighting. When you enter the submenu the lights will turn on, if not on already, in a colorblending mode.

Note: The lights automatically turn off after 2 hours. They can be reactivated if needed.



Figure 11.2a




Figure 11.2b



- Intensity Control Button: Press to activate and adjust the intensity of the lights. This will only work with the solid color option. The range is from 0 to 5. To turn off the lights, the intensity level must be decreased to 0.
 - Tap to raise the intensity of the lights to the maximum level of 5. The intensity levels are as follows: 5 = 100%, 4 = 80%, 3 = 60%, 2 = 40% and 1 = 20%, 0 = 0%.
 - Tap to lower the intensity of the lights to the minimum level of 0.



- = Speed Control Button (Increase): Controls the blending speed for the lights.
 - Tap ▲ to increase the blending speed, of the colors, to the maximum speed of 5. The speed settings are as follows:
 5 = every 5 secs, 4 = every 10 secs, 3 = every 15 secs,
 2 = every 30 secs and 1 = every 60 secs.
 - Tap to decrease the blending speed, of the colors, to the minimum speed of 0.



- **Exterior Light Button:** Controls the exterior lights. The only light color option is white.
 - Tap once to turn the lights on at a low intensity. Tap again to turn the lights on at a high intensity. Tap again to turn lights off.

Note: This feature is only available with the SunSide™ cabinet option. Not available for the Maxxus and Aspen models.



= Home Button: Tap to go back to the Home Menu.



= Invert Button: Tap to invert the display image.



Color Selector: Tap a color to select a single color.

11.3 Music Menu

Models equipped with the optional Audio System offer an enhanced spa experience. The BLUEWAVE® 2.0 Wireless Audio System works with most Bluetooth® wireless devices. An auxiliary device can be connected, via a 3.5 mm plug cable, located behind the front cabinet panel, if a Bluetooth device is not available. These models also include four high fidelity spa engineered speakers for unsurpassed sound quality and long-life, and an integrated powered subwoofer for a superb acoustical sound. **Note:** If the spa does not have the stereo option, there will not be a button on the control panel.

To access the Music Menu, tap (4)), Figure 11.3a. The display will change to Figure 11.3b. Once you enter the Music Menu, tap the power button to turn the stereo on. Your connected electronic device, Bluetooth or auxiliary, provides the audio entertainment.



WARNING: RISK OF ELECTRICAL SHOCK HAZARD EXISTS AND EQUIPMENT DAMAGE! Never install or remove electrical devices while hands are wet or while sitting partially immersed or fully immersed in spa!





Figure 11.3a

Figure 11.3b



= Power Button: Tap to turn the stereo on and off.



Bluetooth Settings: Displays when a Bluetooth device is connected with the stereo.



 Auxiliary Settings: Displays when an Auxiliary device is connected with the stereo.



= Volume Up: Tap to increase the volume. The range is from 0 to 30 in increments of 1.



Volume Down: Tap to decrease the volume. The range is from 30 to 0 in increments of 1.



= Forward: Tap to advance forward through tracks.



= Rewind: Tap to move back through tracks.



= Pause/Play: Tap to pause and play tracks.

Track Name = Artist Track: Will display the artist and track information, if it is available. If the information is not available this part will be blank. If the information provided is too long, the maximum number of characters will be display follow by dots ("...").



= Audio Settings: Tap to access the audio submenu, page 53.

Volume = **Volume**: Displays the current volume level from 0 to 30.



= Back Button: Tap to go back to the Home Menu.



= Invert Button: Tap to invert the display image.

11.4 Connecting the BLUEWAVE® System with your Bluetooth® device

A. To bridge a connection between the BLUEWAVE 2.0 Wireless Audio System and your Bluetooth® device, follow the steps below.

Note: The BT icon cannot be selected manually unless a Bluetooth connection is established with your device. If you experience a connection problem with your Bluetooth device, make sure that the Bluetooth antenna is secure and located at the highest point within the equipment bay.

- Tap the music icon on the control panel screen then tap the power button.
- From your Bluetooth device, make sure that the Bluetooth setting is ON.
- 3. Follow the pairing instructions for your Bluetooth device and connect to the "BLUEWAVE" device that appears on your screen.___
- 4. Once the connection is established, the Bluetooth icon () on the screen will be display confirming the connection.
- 5. If asked for a password, enter the password "0000" and then tap "Pair" on your device to connect.
- 6. If the pairing process is successful, your Bluetooth device will show "Connected" right next to "BLUEWAVE."
- B. Connecting an Auxiliary Device
- 1. Remove the front panel.
- 2. Locate the BLUEWAVE unit in the equipment bay.
- 3. Locate the cable labeled "AUX" that is connected to the unit.
- 4. Use a 3.5 mm cable (not included) to connect your auxiliary device.
- 5. Run the cable safely, through the front, and reinstall the panel.

Note: Use caution in handling the auxiliary device, the placement of the device, and that the cable is not in the way.

11.5 Audio Settings Menu

To enter the Audio Settings Menu, tap ▶ from the Music submenu, Figure 11.5a. The display will change to Figure 11.5b. The Audio Settings Menu offers an enhanced audio experience by providing a custom or preset listening settings.






Figure 11.5a

Figure 11.5b



Treble Selection: Tap to adjust the treble setting to create a custom sound.



= Bass Selection: Tap to adjust the bass setting to create a custom sound.



= Bass/Treble Adjustment Bars: Tap ▼ or ♠ to adjust the Bass/Treble range from -5 to 5. This feature can be used to create a custom sound.



= Rock Preset: Tap to activate the "Rock" music audio setting. "Rock" has a 4 Bass and 3 Treble preset setting.



Pop Preset: Tap to activate the "Pop" music audio setting. "Pop" has a 2 Bass and 2 Treble preset setting.



Classical Preset: Tap to activate the "Classical" music audio setting. "Classical" has a 3 Bass and 3 Treble preset setting.



= Back Button: Tap to go back to the Home Menu.



= Invert Button: Tap to invert the display image.

11.6 CLEARRAY on Demand

The CLEARRAY on demand feature activates the water purification system for a period of 1-hour. Tap to turn the system on. During this time the circulation pump and the CLEARRAY unit are on.

Note: When the CLEAR**RAY** system is on due to a programmed or scheduled setting the feature cannot be turned off.

11.7 Selecting The Desired Massage Action

Your Sundance® Spas hot tub is equipped to allow you to customize the massage action you desire. Each model incorporates a massage selector(s) that allows you to customize the massage and performance by diverting water between various jet systems. Simply turn massage selector to position A (Combo), B, or C to divert water pressure to various jet groups.


Note: This valve is designed to operate in positions A (Combo), B, and C for optimum performance. It is considered normal for sound levels within the valve to vary between positions due to the large amounts of water flowing through it. For optimum filtration benefits, leave the valve in position A when hot tub is covered. Select position B or C for maximum jet performance during hot tub use.


11.8 Adjusting Fluidix Reflex, Nex, ST, Intelli-Jets And Focus-Relief


The jets in your new hot tub offer the advantage of no moving parts and zero maintenance. They can also be adjusted for a high and low impact massage, providing the ultimate massage! To adjust jets:

Fluidix Nex/Intelli-Jets and Reflex Jets only: Turn outer dial

 (A) clockwise to increase water volume. Turn outer dial counterclockwise to decrease water volume or to shut jet off.







11.9 Air Controls

Each jet system has its own air control. These controls allow you to regulate the amount of air which is mixed with the water entering through the jets. Clockwise rotation adds more air and counterclockwise rotation reduces air flow.

Note: To minimize heat loss, close all air controls when spa is not in use. Certain jets may draw air even though they are closed. This is considered normal.



Fluidix Reflex Jet



Eluidiy ST Int



Focus-Relief Jet

11.10 Waterfall Control

Turn waterfall control valve counterclockwise to increase waterfall(s) output. Turn control valve clockwise to decrease or turn off waterfall(s) output. The waterfall is on when the circulation pump is running.



Note: It takes 2 full revolutions to change the waterfall from a full off to a full on flow rate. When the waterfall is in the OFF position some water may still flow through. This is considered normal.

11.11 Fragrance Dispenser

On the rim of your hot tub is a screw-off cap labeled "SunScents™ Fragrance Dispenser" (pages 22-40). It is designed to contain packages of a specially made fragrance available from your Sundance Spas dealer. The fragrance is carried into the hot tub water by the air coming through the injector system when the air blower is on.



WARNING: TO DECREASE RISK OF PERSONAL INJURY.

- Always turn off the air blower before removing or installing SunScents dispenser cap to reduce the risk of by having the dispenser and/or cap fly up.
- Use only Sundance SunScents fragrances in your new hot tub, as the tub has not been tested for use with any other manufacturer. Never use this dispenser for any other type of fragrance.
- Never remove the SunScents beads from their plastic cage for any reason! This can cause damage to the spa equipment and plumbing lines.
- The beads can also be ingested creating a chocking or poisoning hazard. Keep away from children.
- Install bead cage directly into SunScents dispenser.
- Always make certain that the dispenser cap is securely in place before operating the hot tub's air blower, to avoid the cap from flying off when the blower is activated.

11.12 Indicator Light

The indicator light located on the front cabinet panel of the hot tub is an early detection system that will notify you when the hot tub needs immediate attention. A solid white light indicates that all operations are normal. A solid red light indicates that immediate attention is required to clear or fix an error code. For a detailed explanation refer to Section 15.0, page 83.

11.13 Optional Exterior Light (Maxxus and Aspen Models Only)

The optional exterior lights are located on the corners of the cabinet panels. They provide a colorful luminance around the hot tub. These lights are activated any time the interior lights are being used and will follow the color pattern.

Note: This option is only available as an aftermarket feature for all other 880 models with the standard cabinet panels.

11.14 MicroClean® Plus Versatile Filter Lid

The multi-purpose filter lid can be used as cooler or as a seat (with the optional aftermarket seat cushion).





IMPORTANT! If liquids (other than water) spill, take all precautions to prevent contaminants from entering and affecting the hot tub water.

11.15 Optional SmartTub™ System (60Hz models only)

Advances in technology have allowed us to create a better and smarter hot tub. Our SmartTub™ system operates on a cellular network. The advantages of this system are:

- A more stable connection to internet for outdoor environment.
 The SmartTub™ device uses much less data than a typical voice connection via cellular networks. We contract through the largest wireless carriers to ensure maximum uptime. The system enables firmware updates via the cell connection so your system's performance will continuously be optimized remotely.
- Maintenance is made easy by alerts sent to your phone.
- Diagnostic alerts are sent to you and your dealer when attention is required.

A. Pairing process

- Download the SmartTub™ app from the Google Play store or Apple App store.
- 2. Open the app and create an account.
- 3. Locate the SmartTub™ sticker next the control panel of the hot tub. You can either scan the QR code with the SmartTub™ app or manually input the serial number located below the QR code on the sticker.
- 4. After you pair the hot tub's serial number to the SmartTub™ app, the app will load and connect the hot tub to the internet.
- 5. Follow the instructions on the app to begin enjoying the benefits of your internet connected hot tub.

Note: The first year of data service is included. You will need to renew the subscription after the first year. Please refer to the terms of service and privacy policy links in the SmartTub™ app for additional information.

B. Indicator Lights


There are indicator lights on the SmartTub™ controller that relay the status of the system. Below are meanings of the lights.

1. Cloud:

- Blue light on connected to cloud.
- Blue light off not connected to cloud.

2. Spa:

- Blue light on connected to spa controller
- Blue light off not connected to spa controller



Status:

- Cyan light breathing (slow pulsing) indicates the status is good.
- Cyan light flashing indicates that the system is completing a connection to the cloud.
- Green light flashing indicates waiting for a connection to the cellular tower.
- Dark blue light flashing indicates a SIM error.

Cell signal strength:

3 blue LED lights indicates cell signal strength.

C. Resetting the SmartTub™ controller

Should the SmartTub™ controller need to be reset, hold the magnet (located on the cord) to the reset label on the side of the SmartTub device.

12.0 Programming and Operation Instructions

Your Sundance spa is equipped with setting menus that allow you to program and activate different components of the spa. With our iTouch™ control panel, programming your spa has never been easier. In the sections that follow, we will guide you through the process of programming the spa to fit your personal comfort. Tap o to enter the Settings Menu, Figure 12.0a and 12.0b.





Figure 12.0a

Figure 12.0b

Heat & Filter = **Heat and Filter:** Provides access to the heating and filtration programming, page 58.

Water Care = Water Care: Provides access to the water care programming, page 62.

Wi-Fi = Wi-Fi: Provides access to the Wi-Fi settings, page 64 (50Hz Models only).

Lock = **Lock**: Provides access to activate the locking features, page 65.

Time & Date = **Time and Date**: Provides access to the time and date programming, page 66.

Language

= Language: Provides access to the language programming, page 67.

Units

 Units: Allows access to the temperature display feature, either in Fahrenheit or Celsius, page 68.
 Default setting is Fahrenheit.



= Home Button: Tap to go back to the Home Menu.



= Back Button: Tap to go back to the previous Menu.



= Invert Button: Tap to invert the display image.





= Scroll Buttons: Scroll up and down to view the selections available.

12.1 Programming the Heating Mode

Your Sundance spa is equipped with 3 modes of heating, Figure 12.1a. An automatic mode called "Auto" where the spa's temperature is maintained at all times. An energy saving heating cycle called "Economy." A mode that will only activate the heater during the daytime called "Day" mode.

Note: The heater will activate when the temperature drops 2°F from the set temperature.





From the Settings Menu, tap ∇ or \triangle to highlight the "Heat & Filter" menu tab. Tap Heat & Filter to the enter the menu. Then select one of the heating settings.

A. Auto heating:

- 1. When programmed to "Auto," the spa will maintain the water temperature to the set temperature. Heating will occur when necessary.
- 2. To select this mode, tap the "Auto" tab.



Figure 12.1a

B. Economy heating:


- 1. This is an energy saving heating program that allows the spa to heat during non-peak hours. When programmed to "Economy," the spa will only be allowed to heat the water between 5:00 PM to 7:00 AM every day of the week. The hours cannot be adjusted.
- 2. To select this mode, tap the "Economy" tab.

C. Day heating:

- When programmed to "Day," the spa will only be allowed to heat the water between 7:00 AM to 5:00 PM every day of the week. The hours cannot be adjusted.
- 2. To select this mode, tap the "Day" tab.

12.2 Programming the Primary Filter

To access the "Primary Filter" feature, tap from the Heat and Filter menu, Figure 12.2a, to enter the "Primary Filter" programming, Figure 12.2.b.






Figure 12.2a

Figure 12.2b

During a primary filtration, the circulation pump, CLEARRAY and ozone unit (if applicable) are activated. The factory default cycle starts at 12:00 AM and last for 8 hours. If you elect to keep this setting, then you can skip this section.



In extreme bitter cold weather, where freezing can occur, we recommend you program the circulation pump to run 24 hours. Refer to the "Winterizing" section on page 76.

Any time the circulation pump runs outside of a program cycle, e.g. for heating, that run time will be deducted from the next primary filter cycle. For example, the primary filter cycle is set to 8 hours every 24 hours but the circulation pump comes on for 2 hours to heat the water after the cycle has finished. The next primary filter cycle will only be for 6 hours not 8 hours.

A. To change the default cycle:

When you enter the menu, certain icons will be highlighted, Figure 12.2c.

Note: If \boxtimes is pressed, in the middle of programming, it will clear the changes made and revert to the prior programmed settings. This feature can be used to make corrections.



Primary Filter

A∀

Figure 12.2c

- Tap ▼ or ▲ to change the hour in 1-hour increments. To switch from "AM" to "PM" you must round a 12-Hour period.
- 2. Tap led to accept and save the change.
- 3. Tap to program the end time for the cycle.
- 4. Tap ▼ or ▲ to change the hour in 1-hour increments. To switch from "AM" to "PM" you must round a 12-Hour period.
- 5. Tap led to accept and save the change.
- 6. Tap \sqrt{s} to return to the Heat and Filter Menu. Tap again to return to the Settings Menu.

Summer Logic: In warm weather, the water temperature in the spa may exceed the set temperature. This condition may occur due to heat transference from the filter/circulation pump and jets pumps. If the water temperature is higher than 95°F (35°C) and rises 2°F above the set temperature, a "Summer Logic" condition occurs that deactivates the filter/circulation pump and CLEARRAY®. This safety feature cannot be altered! The filter/circulation pump and CLEARRAY® will remain off until the water temperature cools to the set temperature (except between 9am-11am when the filter/circulation pump runs for it's mandatory 2 hour cycle.) To help prevent a "Summer Logic" condition, it may be necessary to reduce filter/circulation pump cycles run times in warm weather.

12.3 Programming the Secondary Filter

To access the "Secondary Filter" feature, tap [2] from the Heat and Filter Menu, Figure 12.3a, to enter the "Secondary Filter" programming, Figure 12.3b.




Figure 12.3a




Figure 12.3b

During a secondary filtration, the Jets Pump 1 is activated. There are 3 cycles you can select from, Figure 12.3b. The factory default cycle is "Away Mode." If you elect to keep this setting, then you can skip this section.

A. To change the Secondary Filter cycle:

- Away Mode: Secondary Filtration is disabled. To activate this mode, tap the "Away" tab. This is the factory default setting.
- Infrequent Mode: Activates two cycles at 8:00 PM and 8:00 AM <u>every other day</u>. Each cycle will last 10 minutes for a total of 20 minutes every other day. To activate this mode, tap the "Infrequent" tab. Time and duration cannot be altered.
- Frequent Mode: Activates two cycles at 8:00 PM and 8:00 AM <u>every day</u>. Each cycle will last 10 minutes for a total of 20 minutes every day. To activate this mode, tap the "Frequent" tab. Time and duration cannot be altered.
- Tap to return to the Heat and Filter Menu. Tap again to return to the Settings Menu.

12.4 Cleanup Cycle

The cleanup cycle occurs once per day at 12:00 pm (noon). This is not user programmable. Turning off the corresponding jets pump that is running can deactivate the feature.

- One Pump System Jets Pump 1 and the Circulation Pump turn on for 1 minute and then shut off. Then the blower turns on for 1 minute and then shuts off.
- Two Pump System Jets Pump 1 and the Circulation Pump turn on for 1 minute and then shut off. Then Jets Pump 2 turns on for 1 minute and then shuts off. Then the blower turns on for 1 minute and then shuts off.
- Three Pump System Jets Pump 1 and the Circulation Pump turn
 on for 1 minute and then shut off. Then Jets Pump 2 turns on for 1
 minute and then shuts off. Then Jets Pump 3 turns on for 1 minute
 and then shuts off. Then the blower turns on for 1 minute and then
 shuts off.

12.5 Blow-Out Cycle

This cycle will purge the air from the plumbing lines normally caused by draining and filling the spa. The Jets Pump 1 and the Circulation Pump will turn on for 1 minute and then shut off. Then Jets Pump 2 will turn on and run for 1 minute then shut off. Lastly, Jets Pump 3 will turn on and run for 1 minute then shut off. Turning off the corresponding jets pump that is running can deactivate the feature. This cycle will **only** occur at start up and after exiting a service lock.

12.6 Water Care Programming

Water care is crucial to maintaining a healthy and clean spa. The CLEAR**RAY** water purification system leads the way by sanitizing the water using a UV light bulb. Your spa can be programmed to remind you when to check and replace certain components.

From the Settings Menu, tap \checkmark or \land to highlight the "Water Care" menu tab, Figures 12.6a and 12.6b. Tap \checkmark to the enter the menu. Then select one of the features.





Figure 12.6a

Figure 12.6b

A. Programming the CLEARRAY® UV Bulb Timer

The CLEARRAY UV bulb has a life expectancy of 1 year. A timer activates when power is applied and begins a countdown starting at 365 days. Once the timer expires, an error message will appear on the display, the UV bulb must be replaced and the timer needs to be reset. Tap CLEARRAY 65 (Figure 12.6c) to enter the Programming Menu.

Note:

- The days are stored in memory if the power is interrupted.
- The CLEARRAY UV timer counts down by days not usage.
- From the "Water Care" Menu you can to set the CLEARRAY UV bulb timer, Figure 12.6c.
- Tap ▼ or ▲ to change the days in 10-day increments. The range is from OFF to 365 days. It is not recommended that this feature be turned OFF. In order to continually have the CLEARRAY system effectively preform its function, it should be program as instructed.



Figure 12.6c

Note: Pressing will clear any current changes made. The days will revert to the previous programmed setting. This feature can be used to make corrections.

- 3. Tap 🗵 to confirm and save your changes.
- 4. Tap to return to the "Water Care" Menu. Tap again to return to the Settings Menu.
- 5. When the timer expires, a message will appear on the control panel display. The CLEARRAY UV bulb must be replaced (page 79) and the timer must be reset. Tap "reset" and follow the instructions above to reset the timer. If you tap "snooze" the message will clear but the error icon A will display and the reminder screen will reappear in 10 days.

B. Programming the Water Refresh Timer

A programmable "Water Refresh" reminder can be set to remind you when to drain and refill the spa. Tap Water Refresh 60 (Figure 12.6b) to enter the Programming Menu.

- 1. From the "Water Care" Menu you can to set the "Water Refresh" timer, Figure 12.6d.
- 2. Tap ▼ or ▲ to change the days in 30-day increments. The range is from OFF to 180 days. It is not recommended that this feature be turned OFF. In order to continually maintain the water healthy and clean, in addition to chemical maintenance, it should be program as instructed.



Figure 12.6d

Note: Pressing will clear any current changes made. The days will revert to the previous programmed setting. This feature can be used to make corrections.

- Tap I to confirm and save your changes.
- 4. Tap \(\) to return to the "Water Care" Menu. Tap again to return to the Settings Menu.
- 5. When the timer expires, a message will appear on the control panel display. The water must be drained and replaced with fresh water. Follow the instructions above to reset the timer. If you tap "snooze" the message will clear but the error icon A will display and the reminder screen will reappear in 10 days. Refer to Section 13.3, page 73, for filter location.

C. Programming the MicroClean® Outer Filter Timer

A programmable filter timer can be set to remind you when to clean or replace the MicroClean Outer Filter. Tap MicroClean Outer 60 (Figure 12.6b) to enter the Programming Menu.

- 1. From the "Water Care" Menu you can to set the MicroClean Outer timer, Figure 12.6e.
- Tap ▼ or ▲ to change the days in 10-day increments. The range is from OFF to 180 days. It is not recommended that this feature be turned OFF. In order to continually maintain clean and working filters, it should be program as instructed.



Figure 12.6e

Note: Pressing will clear any current changes made. The days will revert to the previous programmed setting. This feature can be used to make corrections.

- 3. Tap to confirm and save your changes.
- 4. Tap to return to the "Water Care" Menu. Tap again to return to the Settings Menu.
- 5. When the timer expires, a message will appear on the control panel display. The filter must be cleaned or replaced. Follow the instructions above to reset the timer. If you tap "snooze" the message

will clear but the error icon **A** will display and the reminder screen will reappear in 10 days. Refer to Section 13.1, page 69, for cleaning instructions.

D. Programming the MicroClean® Inner Filter Timer

A programmable filter timer can be set to remind you when to replace the MicroClean Inner Filter. Tap MicroClean Inner 50 (Figure 12.6b) to enter the Programming Menu.

- 1. From the "Water Care" Menu you can to set the MicroClean Inner timer, Figure 12.6f.
- Tap ▼ or ▲ to change the days in 10-day increments. The range is from OFF to 90 days. It is not recommended that this feature be turned OFF. In order to continually maintain clean and working filters, it should be program as instructed.



Figure 12.6f

Note: Pressing will clear any current changes made. The days will revert to the previous programmed setting. This feature can be used to make corrections.

- 3. Tap leto confirm and save your changes.
- 4. Tap to return to the "Water Care" Menu. Tap again to return to the Settings Menu.
- 5. When the timer expires, a message will appear on the control panel display. Follow the previous instructions to reset the timer. The filter must be replaced. Refer to Section 13.1, page 69, for filter location. If you tap "snooze" the message will clear but the error icon will display and the reminder screen will reappear in 10 days.

12.7 Optional Wi-Fi Setup (50Hz models only)

From the Settings Menu, tap or to highlight the "Wi-Fi" Menu tab.

Tap Wi-Fi to enter the programming options, Figures 12.7a and 12.7b. Make sure that you have downloaded the Wi-Fi App for this setup.





Figure 12.7a

Figure 12.7b

- You need to follow the instructions from the App in order to connect the Wi-Fi.
- While the system attempts to connect you will see the, "Spa Wi-Fi Setup in-progress," Figure 12.7b. When the connection is done the display will read, "Spa Wi-Fi Setup Successfully Connected."

If the Wi-Fi connection setting should need to be updated or connected to a new router, follow the steps below.

- 1. From the "Settings" menu, tap Wi-Fi (Figure 12.7a) to enter the menu.
- 2. Tap Reset? Figure 12.7b. The display will change to "Spa Wi-Fi Setup In-progress."
- 3. Tap Reset again. This will clear the current data and allow the spa to connect to the new data.
- 4. Reconfigure and setup your spa by following the instructions from the app.

12.8 Locking the Spa

From the Settings Menu, tap or to highlight the "Lock" menu tab. Tap Lock (Figure 12.8a) to enter the programming options, Figure 12.8b. You can prevent users from changing certain features of the spa. When a lock feature is active, the lock icon will appear on the Main Menu.





Figure 12.8a

Figure 12.8b

A. Temp Lock (Figure 12.8b):

- 1. Tap to lock the temperature feature.
- 2. Tap (the first block) to select a number. Use vor to select a number from 0-9. Then move on to the next number until a four-digit code has been selected.
- 3. Tap local to activate the locking feature.
- The adjust temperature feature is disabled, but the spa will still perform all scheduled tasks.
- 5. Tap 🔦 to return to the "Settings" Menu.

B. Spa Lock (Figure 12.8b):

- 1. Tap to lock the spa. When this feature is activated both the spa and temperature lock are highlighted.
- 2. Tap ____ (the first block) to select a number. Use ▼ or ▲ to select a number from 0-9. Then move on to the next number until a four-digit code has been selected.
- 3. Tap leto activate the locking feature.
- 4. All activation and adjustment features are disabled but the spa will still perform all scheduled tasks.
- 5. Tap 🔦 to return to the "Settings" Menu.

C. Service Lock (Figure 12.8b):

- 1. Tap to lock the spa. When this feature is activated all the lock buttons are highlighted.
- 2. Tap ——— (block) to select a number. Use ▼ or ▲ to select a number from 0-9. Then move on to the next number until a four-digit code has been selected.
- Tap to activate the locking feature.
- 4. All spa functions are locked to allow for a temporary service mode such as filter cleaning.

Note: This mode has a time out of 2 hours. The spa should not be left in this lock mode for an extended period. Especially in colder climate or when freezing conditions exist.

D. To Unlock (Figure 12.8c):

- 1. Enter the Lock menu. The type of lock that is active will already be highlighted.
- 2. Tap ____ (the first block) to start entering the code. Then move on to the next number until the four-digit unlock code has been entered.



Figure 12.8c

- 3. Tap 🗵 to unlock.
- 4. Tap 🔨 to return to the "Setting" Menu.

Note: A default passcode can be used in case the original passcode is lost or forgotten. The code "0772" will unlock the locked setting.

12.9 Programming the Time and Date

From the Settings Menu, tap ∇ or \triangle to highlight the "Time & Date" menu tab. Tap Time & Date to enter the programming options, Figures 12.9a and 12.9b.



Figure 12.9a



Figure 12.9b

A. To set the time:

The default time setting is a 12-Hour configuration. To choose the 24-Hour configuration, then tap 🕞 to change the setting.

- 1. When you enter the menu, a few of the icons will be highlighted, Figure 12.9c.
- Tap ▼ or ▲ to change the hour in 1-hour increments. To switch from "AM" to "PM" you must round a 12-Hour period.
- 3. Tap the minute block 8: 1 to program.
- Tap ▼ or ▲ to change the minutes.
- 5. Tap 🗵 to confirm and save your changes.

B. To set the date:

Each setting for month, day and year can be set independently.

- 1. Tap to program the date, Figure 12.9d.
- 2. Tap the month block \(\bigcirc \big
- Tap ▼ or ▲ to make changes.
- 4. Tap the day block 12/10/2015 to program.
- Tap ▼ or ▲ to make changes.
- 6. Tap the year block 12/10/2015 to program.
- Tap or to make changes.
- 8. Tap to save and accept the changes.
- 9. Tap to return to the "Settings" Menu.



Figure 12.9c



Figure 12.9d

12.10 Programming the Language

From the Settings Menu, tap or to highlight the "Language" menu tab. Tap Language to enter the language options, Figures 12.10a and 12.10b.



Figure 12.10a




Figure 12.10b

- 1. There are 4 languages to select from: English, French, Deutsch, and Español. To select a language, tap the language tab you want to display, Figure 12.10b.
- 2. Tap 🔨 to return to the "Settings" Menu.

12.11 Units Display

From the Settings Menu, tap ∇ or \triangle to highlight the "Units" Menu tab. Tap Units to enter the selection menu, Figures 12.11a and 12.11b.

- 1. Tap the unit of measure tab that you want to display.
- 2. Tap 🔦 to return to the "Settings" Menu.







Figure 12.11a

Figure 12.11b

12.12 System Information

This menu will display the current information for the spa. From the Settings Menu, tap or to highlight the "Information" Menu tab. Tap to enter the selection menu, Figures 12.12a and 12.12b. There are no selections that can be made. The menu simply provides information.








Figure 12.12b

13.0 Hot Tub Maintenance

Proper and regular maintenance of your hot tub will help it retain its beauty and performance. Your authorized Sundance Spas dealer can supply you with all the information, supplies, and accessory products you will need to accomplish this.

<u>^i\</u>

DANGER: RISK OF SEVERE INJURY OR DROWNING BY ENTRAPMENT!

- Keep hair, loose articles of clothing or hanging jewelry away from suction fittings, rotating jets or other moving components to avoid entrapment that could lead to drowning or severe injury.
- Never use the spa unless all suction guards, filter, filter lid, or skimmer assembly are installed to prevent body and/or hair entrapment.
- Never operate or use the spa if the filter, filter lid, or skimmer assembly are broken or any part of the skimmer assembly is missing. Please contact your dealer or nearest service center for service.
- The suction fittings and suction covers in this spa are sized to match the specific water flow created by the pump(s). If it is necessary to replace the suction fittings, suction covers or pump(s), be sure that the flow rates are compatible and are in compliance with the VGB Safety Act, page 2.
- Never replace a suction fitting or suction cover with one rated less than the flow rate marked on the original suction fitting. Using improper suction fittings or suction covers can create a body or hair suction entrapment hazard that may lead to drowning or severe injury.
- Owners must alert all spa users to the potential risk of Hair, Limb, Body, Evisceration (disembowelment), and Mechanical Entrapment, page 7.

13.1 Cleaning/Replacing the Filter Cartridge A reminder message appears on the control panel display, after a specified number of days, to remind you to clean the MicroClean® Ultra filters. This reminder must be reset at each interval. Refer to Section 12.6, for additional information and programming details.



Your Sundance hot tub is equipped with a two-stage MicroClean Ultra filter cartridge assembly under the filter lid (Sections 9.1-9.22 pages 22-40). Debris is filtered by the filter/circulation pump drawing water through the filter assembly 8 hours a day, 7 days a week (unless programmed otherwise). To ensure optimum performance, clean the outer pleated filter and center insert monthly. Then replace the center insert every 6 months, or as needed thereafter.

All models include a suction cover filter (#6540-213) located directly under the MicroClean Ultra filter cartridge assembly that prevents debris from entering the hot tub plumbing when jets pump 1 is running. This filter should be cleaned every 2 months.



TO DECREASE RISK OF DEATH, DROWNING, OR ENTRAPMENT, ALWAYS TURN POWER TO THE HOT TUB OFF BEFORE REMOVING THE MICROCLEAN ULTRA FILTER ASSEMBLY!


Filter Cleaning/Replacement Procedure:





DANGER: TURN POWER TO SPA OFF! TO DECREASE RISK OF DEATH, DROWNING, OR ENTRAPMENT, NEVER OPERATE SPA WHEN FILTER IS NOT PROPERLY INSTALLED OR IF WEIR ASSEMBLY IS DAMAGED OR ALTERED!





Filter Cleaning Requirements:

- Clean MicroClean Ultra Pleated Filter (1) monthly and replace every 18 months (6473-165).
- Rinse off MicroClean Ultra Insert (2) monthly and <u>replace every 6 months</u> or as needed (6473-164).

Filter Removal Instructions:

Loosen filter nut to provide clearance, then remove MicroClean Ultra Filter Assembly from spa.




Monthly Filter Cleaning Procedure

We recommend cleaning the outer pleated filter (1) with a high pressure water nozzle and the filter insert (2) with a low-pressure water nozzle monthly. Periodically, the outer pleated filter cartridge (1) will require a more thorough cleaning to remove embedded oils and minerals by using special spa filter cleaners offered by your spa dealer. Always remove the center filter insert (2) before cleaning the outer filter (1) with chemicals. Never use filter cleaners of any kind on the filter insert (2) or it may be damaged, come apart or allow impurities to re-enter the water, increasing the risk of contracting a waterborne illness (e.g. an infection, bacteria or virus) and/or respiratory ailments.

Procedure:

- 1. Grasp center filter insert end cap (2) in hand and pull outward from pleated cartridge (1). If filter insert (2) is 6 months old, throw it away and purchase new one. DO NOT install new insert at this time.
- Rinse debris from all outer filter

 pleats using a garden hose and high-pressure nozzle. Repeat process until all filter pleats are clean. Then rinse debris from inside of filter (1). If chemical cleaners are used, follow manufacturers instructions.



Lightly rise filter insert (2) and place in clean location. *DO

NOT use chemical cleaners or high-pressure nozzle on insert (2) or it may be damaged, come apart or allow impurities to re-enter the water, increasing the risk of contracting a waterborne illness (e.g. an infection bacteria or virus) and/or respiratory ailments.

- Install filter insert (2) into outer pleated filter (1) by gently sliding inward until a slight resistance is felt approximately 1/4" from bottom. Lightly tap insert end with palm of hand to "snap" in place. Insert is properly installed when end cap rests "flush" against outer filter end cap.
- Install Filter assembly back into spa by performing step 2 in reverse order. Tighten filter nut so it just touches the filter face. DO NOT OVERTIGHTEN!
- 5. Turn power to spa back on.

Replacement filter cartridges may be purchased from your Sundance Spas dealer.

13.2 Removing the Cabinet Panels

A. Quick Release Door (Except Maxxus and Aspen Models)

The Quick Release Door provides easy access to the equipment bay and components without having to unscrew the panel. To remove the Quick Release Door follow the steps below:

Note: For the Maxxus and Aspen models the front panel must be unscrewed to be removed.






Figure B

- 2. Press the buttons to release the panel from the spa frame, Figure B.
- 3. Slowly and gently tilt the panel forward to remove. This will expose the equipment bay for easy access to components like the CLEARRAY System and the Quick Drain Valve, Figure C. Place the panel in a safe location to prevent

Figure C

4. To reinstall the panel just follow the steps above in reverse order.


B. SunSide™ Skirt Panel Removal (Except Maxxus and Aspen Models)

from damaging it.

The SunSide Skirt panels provide easy access to the equipment bay and components without having to unscrew the panel. To remove the skirt panels follow the steps below:

Note: For the Maxxus and Aspen models the front panel must be unscrewed to be removed.

 Grab one of the corner panels, from the bottom, where it touches the bottom pan. Then gently pull the panel forward to unsnap it from the holding clip then pull down to remove, Figure D. Place the panel in a safe location to prevent from damaging



it. Repeat the steps to remove the other corner panel.

Note: The corner exterior lights on the panels are are connected to the light wires. Take care when removing the corner panels to avoid damaging the wires.

- Grab the bottom of the panel and slightly lift to release it from the top mount. Tilt the panel and pull down to remove, Figure E. Place the panel in a safe location to prevent from damaging it.
- 3. To reinstall the panel just follow the steps above in reverse order.

13.3 Draining And Refilling

Every 3 months, you will need to replace the hot tub's water. The vfrequency depends on a number of variables including the amount of use, attention paid to water quality maintenance, etc. You will know it is time for a change when you cannot control sudsing and/or you can no longer get the normal feel or sparkle to the water even though the key water balance measurements are all within the proper parameters.



CAUTION! READ THIS BEFORE DRAINING: To decrease damage to the hot tub's components, turn off power to the hot tub at the circuit breaker before draining it. Do not turn the power back on until your hot tub has been refilled. There are certain precautions to keep in mind when draining your hot tub. If it is extremely cold, and the hot tub is outdoors, freezing could occur in the lines or the equipment (see "Winterizing," page 76). On the other hand, if it is hot outdoors, do not leave the hot tub's surface exposed to direct sunlight for long periods.

A. Draining Procedures (SunStrong® Cabinet):

- 1. Turn off power to hot tub at breaker.
- 2. Locate the 3" gray drain valve cap on side of the hot tub cabinet. Unscrew drain valve cap to expose the underlying male garden hose fitting (Figures A-B).
- 3. Attach female garden hose end to drain fitting and route opposite end of garden hose away from hot tub (Figure B).
- 4. Pull outward on garden hose end at drain connection (approx. 3/8") to open drain valve and release water from hot tub (Figure C). Water drains at approximately 3 gallons per minute.
- After hot tub has drained, close drain valve by pushing inward on garden hose end at drain connection until you feel it bottom out. Remove garden hose and install gray drain cap before refilling hot tub.

Note: The gray drain cap cannot be installed until the drain valve is closed. Refer to "Hot Tub Fill Up Procedure" (page 17) for recommended filling instructions.

B. Draining Procedures (SunSide™ Cabinet):

- 1. Turn off power to hot tub at breaker.
- Locate drain hose line attached to the 2 x 4 wood slat, Figure D. Hold drain hose above water line. Unscrew drain valve cap to expose the underlying male garden hose fitting, Figure E.
- Attach female garden hose end to drain fitting and route opposite end of garden hose away from hot tub.
 Note: Make sure to direct water away from hot tub.



Figure A





Figure D


- 4. After spa has completely drained, reinstall drain cap on drain valve finger tight! DO NOT OVERTIGHTEN!
- 5. Place drain hose back inside the spa equipment bay.


Note: Refer to "Hot Tub Fill Up Procedure" (page 17) for recommended filling instructions.


C. Draining Procedures (Quick Drain):

- 1. Turn off power to hot tub at the breaker.
- Remove the front panel, see page 71 for instructions.

Note: For the Maxxus and Aspen models the front panel must be unscrewed to be removed.












Figure F



Figure (



Figure H

13.4 Cleaning The Hot Tub Interior

To preserve the sheen of your hot tub's surface, it is crucial that you avoid using abrasive cleaners or cleaners which have adverse chemical effect on the surface. If you are not certain as to the suitability of a particular cleanser, consult your authorized Sundance Spas dealer. Regardless of the cleanser used, use extreme care to assure that no soap residue is left on the surface. This could cause severe sudsing when the hot tub is refilled.

13.5 Pillow Care

Remove and clean the headrest pillows as needed with soapy water using a cloth or soft-bristle brush. Always remove the pillows when adding chemical shock treatment to the spa water. The pillows can be returned to the spa when the sanitizer reading is stable as recommended on the inside cover of the manual.

Note: Actual pillow could vary from image shown.



Place both hands on pillow with thumbs as shown.



Press inward with thumbs to curl pillow lip inward so you can grab it with fingertips.



Flex pillow lip inward 2-3" to get a good grip on the ends.



Gently pull outward on pillow to release mounting stud from receptacle on spa shell.

Wash pillow(s) in a mild detergent soap and warm water solution. Never machine wash your pillows or attempt to clean them with a cleaning agent!

To reinstall pillows: Simply align pillow over mounting stud receptacle, then gently push inward to snap in place.

13.6 Maintaining the Hot Tub Cabinet

The hot tub cabinet require little or no maintenance of any kind. To clean, wipe cabinet with a clean towel and mild detergent soap solution.



CAUTION: Never spray cabinet with a high pressure garden hose for any reason since this action may induce an electrical short in the hot tub's electrical equipment.

13.7 Cover Care And Maintenance

Certain hot tub covers distributed by Sundance Spas, Inc., have a vinyl or SUNSTRONG™/SUNSTRONG™ Extreme encasement. This vinyl or SUNSTRONG/SUNSTRONG Extreme encasement also referred to as the cover "skin" is attractive and durable. Regular monthly cleaning and conditioning (vinyl) is strongly recommended and may increase the longevity of your cover.

A. To clean and condition the encasement (cover skin):

- 1. Use a garden hose to remove any debris.
- 2. Using a large sponge or soft bristle brush, use diluted or mild soap to gently scrub the top.
- 3. Rinse and clean and do not allow soap to dry on the cover. Do not use soap on the underside of the cover.
- 4. Please check with your Sundance® spa dealer for recommended cover care and conditioning products. Use non-petroleum based conditioners to keep the vinyl supple.
- 5. Do not use any solvents, abrasive cleaners or strong detergents. Do not use products that contain silicone or alcohol.

B. Additional Care and Maintenance Instructions:

- 1. Debris can accumulate on the spa cover. Removal of snow or other debris will help to avoid breakage of the foam cores.
- 2. Be sure to lock the cover straps to secure the cover from unwanted or accidental entry.
- 3. Do not place heavy objects on the vinyl.

- 4. Do not walk, sit or stand on the cover.
- Do not drag or use the flaps/skirt or the cover lock straps to remove the cover.
- 6. Use only recommended cover lift systems.
- 7. Use only chemicals and cleaners recommended by Sundance Spas.
- 8. Remember to keep spa covered when not in use. Maintaining proper water levels assures efficient operation and efficient electrical usage.
- Do not expose your spa to the sun for extended periods of time as UV rays can damage the interior surface.
- Use caution when removing cover. Before removing cover, assure all locks have been released to avoid lock breakage and/or cover strap damage.

13.8 Winterizing

Your Sundance hot tub is designed to automatically protect itself against freezing when operating properly. During periods of severe freezing temperatures, you should check periodically to be certain that the electrical supply to the hot tub has not been interrupted. In extreme bitter cold weather, less than 32°F (0°C), program the circulation pump to run for 24 hours to prevent freezing.

If you do not intend to use your hot tub, or if there is a prolonged power outage during periods of severe freezing temperatures, <u>it is important</u> that all water be removed from the hot tub and equipment to protect against damage from freezing.

Expert winterization of your spa is highly recommended, contact your authorized Sundance Spas dealer. In emergency situations, damage can be minimized by taking the following steps:

CAUTION: TURN OFF POWER TO HOT TUB!

- 1. Follow the directions (Section 13.3) for draining the hot tub.
- 2. Turn the massage/diverter selector(s) to the middle combo position to allow the water in the plumbing lines to drain, page 54.
- 3. Turn the waterfall valve(s) to the open position to allow the water in the plumbing lines to drain, page 55.
- 4. As the water level drops below the seats, use whatever means necessary to get the water out of the recessed seating areas and into the footwell, such as a wet/dry vacuum.
- 5. Open all the air controls and leave them open until you resume use of the spa, page 54.
- When the water level ceases to drop, use whatever means available to remove any remaining water from the footwell, such as a wet/dry vacuum.
- 7. Remove the equipment-side cabinet panels and locate the drain plugs in the front of each pump (Figures A and B, pages 14-15). Remove these plugs to allow the water to drain out of the pumps and heater.

Note: Approximately 1 to 2 gallons will be released during this procedure. Use a wet/dry vacuum or other means to keep this from flooding the equipment compartment. Replace the drain plugs.

- 8. Loosen hose clamp at bottom of heater (Figures A and B, pages 14-15) and pull hose off of heater fitting (twist the hose back and forth while pulling downward). Tip hose down and allow to drain, then reinstall hose and clamp.
- 9. Loosen hose clamp at bottom of CLEARRAY® system and pull hose off of CLEARRAY fitting (twist the hose back and forth while pulling downward). Tip hose down and allow to drain, then reinstall hose and clamp. Remove the cover of the CLEARRAY system to access the UV bulb and quartz tube. Remove and store the UV bulb in a safe location. Remove and dry off the quartz tube then reinstall it. Depending on the length of time, consider replacing the UV bulb when you resume use of your hot tub.
- 10. Re-install cabinet side panels and cover hot tub so that no moisture can enter into it. Consult your Sundance Spas dealer if you have any questions regarding winter use or winterizing.

13.9 Restarting Your Hot Tub in Cold Weather

If you want to start up your hot tub after it has sat empty for a time in freezing temperatures, be aware that the water remaining in certain sections of the piping may still be frozen. This situation will block water flow preventing the hot tub from operating properly and possibly damaging the equipment. We recommend you consult your dealer for guidance before attempting to restart your hot tub under these conditions.

14.0 Water Quality Maintenance

To decrease the risk of contracting a waterborne illness (e.g. an infection, bacteria or virus) and/or respiratory ailments, maintain water quality within specified limits. This will enhance your enjoyment and prolong the life of the hot tub's equipment. Doing so requires regular attention because the water chemistry involved is a balance of several factors. Procrastination in regard to water maintenance will result in poor and potentially unhealthful conditions for soaking and even damage to your hot tub investment. For specific guidance on maintaining water quality, consult your Authorized Sundance Spas dealer who can recommend appropriate chemical products for sanitizing and maintaining your hot tub.



WARNING: FAILURE TO MAINTAIN WATER QUALITY WILL:

- Increase risk of contracting a waterborne illness (e.g. an infection bacteria or virus) and/or respiratory ailments.
- Damage the equipment, components and spa shell, which are not covered under the hot tub's warranty.

CAUTION: Never store hot tub chemicals inside the hot tub's equipment bay. The equipment bay may reach elevated temperatures, this is where high voltage electronic devices are located. This area is not intended for storage of any kind.

14.1 pH Control

pH is a measure of relative acidity or alkalinity of water and is measured on a scale of 0 to 14. The midpoint of 7 is said to be neutral, above which is alkaline and below which is acidic. In hot tub water, it is very important to maintain a slightly alkaline condition of 7.4 to 7.6 pH. Problems become proportionately severe the further outside of this range the water gets. A low pH will be corrosive to metals in the hot tub equipment. A high pH will cause minerals to deposit on the interior surface (scaling). In addition, the ability of the sanitation agents to keep the hot tub clean is severely affected as the pH moves beyond the ideal range. That is why almost all hot tub water test kits contain a measure for pH as well as sanitizer.

14.2 Sanitizing

To destroy bacteria and organic compounds in the hot tub water, a sanitizer must be used regularly. Your Sundance hot tub is equipped with the Brominator™, a special compartment built into the floating skimmer gate to hold the SunPurity™ mineral cartridge designed specifically for your hot tub or bromine tablets. By regulating the number of bromine tablets in the Brominator you can control the amount of bromine, which is actively working, in your hot tub water. A bromine residual of no less than 2.0 ppm is generally considered desirable. A two-part bromine system or granular chlorine (dichlor) are also acceptable sanitizers. When adding spa shock (chlorine or non-chlorine) or pH balancing chemicals, activate the jets pump(s) and leave the spa cover open for a minimum of 20 minutes. By doing this you will allow excess chemical vapors to exit the spa, protecting pillows and plastic knobs from chemical attack.



WARNING: RISK OF PERSONAL INJURY, DROWNING OR ENTRAPMENT!

Never leave your hot tub unattended for any reason while the cover is open and accessible, especially to small children and animals!

CAUTION: RISK OF PERSONAL INJURY OR SPA DAMAGE! Never add chlorine tablets (trichlor) or acid to your hot tub for any reason! These chemical may damage components within your hot tub, burn or irritate your skin, create a rash, and void the manufacturer warranty for your spa.

14.3 CLEARRAY® Water Purification System

Your new hot tub has our water purification system factory installed that will begin disinfecting your water instantly. CLEARRAY Water Purification System is exclusive technology utilizing natural ultraviolet technology to sanitize your water, disinfecting bacteria, viruses, and algae in portable hot tubs. The ultraviolet light otherwise known as UV-C or germicidal light inactivates the microorganisms by disrupting the DNA so that it cannot reproduce and is considered lifeless. The ballast is the power supply for the purification system; it has two LED indicator lights the green indicating incoming power flow and the red indicating the system is properly working. CLEARRAY is standard for all models.



After a year the bulb must be replaced. A message will appear on the LCD display when the time allotted has expired. In order to clear the message, a new UV bulb needs to be installed and the timer must be reset (Sec. 12.6, page 62).




WARNINGS:

- Do not operate the UV-C emitter when it is removed from the appliance enclosure.
- This appliance contains a UV-C emitter.
- Unintended use of the appliance or damage to the housing may result in the escape of dangerous UV-C radiation. UV-C radiation may, even in little doses, cause harm to the eyes and skin.
- Appliances that are obviously damaged must not be operated.
- Read the maintenance instructions before opening the appliance.

14.4 CLEARRAY® Bulb Replacement and Quartz Tube Maintenance

Important: It is **MANDATORY** that the UV bulb is replaced and the quartz tube be cleaned every 12 months to maintain optimum performance.





DANGER: TURN THE SPA BREAKER TO THE OFF POSITION!



DANGER: DRAIN THE SPA IF YOU ARE REPLACING OR CLEANING THE QUARTZ TUBE!



WARNING: ALLOW LAMP TO COOL DOWN PRIOR TO REMOVING FROM QUARTZ TUBE.



DANGER: NEVER LOOK AT THE LIT BULB. THIS CAN CAUSE SEVERE EYE DAMAGE OR BLINDNESS.

UV bulb replacement and quartz tube maintenance:

Note: Location of CLEAR**RAY** System and connection may vary by model.


1. Turn the breaker to the spa OFF. <u>DRAIN YOUR SPA</u>. **Note:** If you are only replacing the UV bulb then the spa does not have to be drained. You will need to drain it if you are replacing or cleaning the quartz tube.

2. Once the UV bulb has cooled off remove the CLEARRAY System enclosure cover (9) and gasket (8) by removing the four screws (10). This will expose the UV bulb and connections, Figure 2.






DANGER: NEVER REMOVE COVER WITHOUT FIRST TURNING OFF AT POWER SOURCE AND DRAINING THE SPA.



- 3. Disconnect UV bulb socket (7) from the power cord socket (11), Figure 3.
- 4. Slowly remove the UV bulb (3) out of the quartz tube, Figure 4.
- 5. Remove the quartz seal compression nut (5) by turning it counterclockwise, Figure 5. Use a pair of channel-lock pliers if needed, Figure 6. You will notice that there is a stainless steel compression washer (4) which slides over the quartz tube, save the washer (4) for later use, Figure 7.



7. <u>Cleaning quartz tube:</u> Clean the quartz tube by wiping, until clear, using a paper towel or a dry cotton cloth. If needed, a household tub and shower lime removal product can be used.



WARNING: Do not use abrasive cleaners as they can scratch the quartz tube surface.

- 8. Rinse the quartz tube with clean water to completely remove any cleaning products that were used in step 7.
- 9. Replacing quartz tube: You will notice that the new quartz tube does not have a black cushion on the domed end as the old quartz tube does. This is normal as the cushion was provided with the original quartz tube to protect it from breakage during transportation. Place the new quartz tube (2) into the water chamber (1) with the domed end first making sure it is inserted and seated inside the quartz end holder. Only a small portion will be exposed when it is seated correctly.
- 10. Reinstall the compression washer (4) over the open end of the quartz tube (2).
- 11. Reinstall and hand tighten the quartz seal compression nut (5) by turning it **clockwise**.
- 12. Refill your spa.
- 13. System Test 1: Assure there is no water dripping from the seal compression nut (5). If water is visible, STOP and tighten the compression nut (5) using a pair of channel lock pliers to a maximum of 1/4 turn. If that does not fix the leak, then repeat quartz tube maintenance process from step 1 through step 12. Make sure there is no water leaking before proceeding to step 14.

- 14. <u>System Test 2:</u> Reconnect the CLEARRAY unit to the controller. Turn breaker back ON. Turn on the pump to circulate the water through the CLEARRAY System. Wait for 5 minutes and assure no water is dripping. If water is visible, STOP, fix the leak by repeating quartz tube maintenance process from step 1 through step 13. <u>Make sure there is no water visible. Turn the pump and breaker OFF BEFORE proceeding to step 15.</u>
- Reconnect the UV bulb socket (7) to the power cord socket (11)
 make sure you use the latex glove provided when handling the UV
 bulb.



WARNING: DO NOT TOUCH THE NEW UV BULB WITH YOUR BARE HAND. Oil on your skin will cause hot spot on the UV bulb and shorten the life of your UV bulb. Use the provided latex glove to handle the UV bulb.

- 16. Slide the new UV bulb (3) back inside the quartz tube.
- 17. Reinstall the black bulb boot (6) back over the quartz seal compression nut (5).
- Reinstall the enclosure cover (9) with gasket (8) and secure with the screws.
- 19. Properly dispose of the old UV bulb.



WARNING: This CLEARRAY System includes a UV bulb, which contains mercury. Dispose of the bulb in accordance with disposal laws. See www.lamprecycle.org.

20. Once power is activated you can check the ballast (12), Figure 8, to see if the CLEARRAY System is functioning; it has two LED indicator lights the green indicating incoming power flow and the red indicating the system is properly working.



FIGURE 8

14.5 Other Additives

Many other additives are available for your hot tub. Some are necessary to compensate for out-of-balance water, some aid in cosmetic water treatment and others simply alter the feel or smell of the water. Your Authorized Sundance Spas dealer can advise you on the use of these additives.

14.6 Handrail Maintenance

The handrails in your Sundance hot tub are manufactured from a high quality 316 stainless steel alloy. Many people are familiar with the term "stainless steel" and are surprised to learn that it does indeed rust and corrode in the presence of chloride salts, free chlorine, or sulfide gasses. The bad news is the environments that produce these elements are ocean spray, salted highways, chemical treatments added to swimming pools and hot tubs, and ground water in numerous coastal areas. The good news is with proper care, your hot tub's handrails can maintain their original finish.

If your stainless handrails shows signs of rusting you should:

- Wash with fresh water (a good detergent won't hurt).
- Clean with a good car chrome polish.
- Wax with an automotive or fiberglass wax.

You should never:

- Clean with chlorinated cleaners or scouring powders.
- Use sand paper, "Scotch Brite," Brillo pads, or similar abrasive products.
- Clean with muriatic or hydrochloric acids. Vinegar is ok, but it won't do much to remove rust.

15.0 Troubleshooting - Display Messages



There are a number of unique functions designed into your Sundance hot tub to protect it from damage and/or to aid in troubleshooting. The indicator light located on the front cabinet panel of the spa is an early detection system that will notify you when the spa needs immediate attention. A solid white light indicates that all operations are normal. A solid red light indicates that immediate attention is required to clear or fix an error code. Following is a listing of all the possible messages along with their meanings. Always insist on genuine Sundance replacement parts.





- Open Flow Switch: The flow switch is open. Heater is disabled. The circ pump's filter is dirty, or an air lock has occurred at the pump intake. Refer to owner's manual for additional information.
- 2. <u>Closed Flow Switch:</u> (Heater is deactivated. The filter/circulation may also be deactivated.) The flow switch is malfunctioning closed. Contact your authorized dealer or service organization.
- 3. <u>Flow Restriction:</u> Heater is disabled, check for dirty filter. Consult the owner's manual for additional information.

Note: Make sure to clean the filter(s) and correct proper water level before contacting your dealer or service organization.

4. <u>Shorted Hi-limit Temp Sensor:</u> The hi-limit temperature sensor is not functional. Heater is disabled. This must be repaired only by a qualified authorized service organization or service technician.

- 5. <u>Open Hi-limit Temp Sensor:</u> The hi-limit temperature sensor is not functional. Heater is disabled. This must be repaired only by a qualified authorized service organization or service technician.
- 6. <u>Shorted Water Temp Sensor:</u> The temperature sensor is not functional. Heater is disabled. This must be repaired only by a qualified authorized service organization or service technician.
- Open Water Temp Sensor: The temperature sensor is not functional. Heater is disabled. This must be repaired only by a qualified authorized service organization or service technician.
- Closed Flow Switch on Start-up: Flow switch is non-functional. Closed or shorted flow switch on system start-up (system disabled). Contact your authorized dealer or service organization.
- 9. <u>Frozen on Start-up:</u> Flow switch is non-functional. Shorted flow switch on system start-up (system disabled) and freeze condition detected. Contact your authorized dealer or service organization.
- 10. <u>Cool Warning:</u> Spa water is more than 20°F/11°C cooler than the temperature set point, the circulation pump and heater will automatically activate to provide freeze protection. The spa will stay in this mode until the water temperature reaches 15°F/8°C below the set temperature. No corrective action is necessary.

Note: The heater icon **\(\)** will be blinking and the error icon **\(\)** will be displayed under the temperature.

- Freeze protection: A potential freeze condition has been detected. No action is required. Jets pump(s) operate until the spa is out of danger. No corrective action is necessary. If condition persists, contact your authorized dealer or service organization.
- 12. Overheat protection: **DO NOT ENTER THE WATER!** Spa water temperature above acceptable limits. Heater is deactivated. Remove spa cover to speed cooling. Contact your dealer or service organization.

Note: The heater icon **\(\)** will be blinking and the error icon **\(\)** will be displayed under the temperature.



13. Overheat protection: **DO NOT ENTER THE WATER!** Hi-limit temperature above acceptable limits. Heater is deactivated. Remove spa cover to speed cooling. Contact your dealer or service organization.

Note: The heater icon \(\sqrt{\text{w}} \) will be blinking and the error icon \(\text{\text{\$\text{\$A\$}}} \) will be displayed under the temperature.

<u>/!\</u>

WARNING: RISK OF HYPERTHERMIA (OVER-HEAT-ING) CAUSING SEVERE INJURY, BURNS, OR WELTS.

14. <u>Watchdog Protection:</u> **DO NOT ENTER SPA!** Spa water temperature above acceptable limits. Your spa is deactivated. Remove spa cover to speed cooling. Contact your dealer or service organization.

Note: The heater icon **\(\)** will be blinking and the error icon **\(\)** will be displayed under the temperature.



WARNING: RISK OF HYPERTHERMIA (OVER-HEAT-ING) CAUSING SEVERE INJURY, BURNS, OR WELTS.

15. <u>Watchdog Protection:</u> **DO NOT ENTER SPA!** Hi-limit temperature above acceptable limits. Your spa is deactivated. Remove spa cover to speed cooling. Contact your dealer or service organization.

Note: The heater icon **\(\)** will be blinking and the error icon **\(\)** will be displayed under the temperature.



WARNING: RISK OF HYPERTHERMIA (OVER-HEAT-ING) CAUSING SEVERE INJURY, BURNS, OR WELTS.

16. <u>Watchdog Freeze Protection:</u> Spa water is below 40°F/4.4°C. Jet pumps operate until the spa is out of danger. Contact your authorized dealer or service organization.

Note: The heater icon $\stackrel{\bullet}{\mathbf{W}}$ will be blinking and the error icon $\stackrel{\bullet}{\mathbf{A}}$ will be displayed under the temperature.

17. <u>Controller Overheat Protection:</u> Controller temperature has exceeded acceptable limits. If condition persists, provide shade for equipment side of spa. Contact your authorized dealer or service organization.

Note: The heater icon **\(\mathbf{h} \)** will be blinking and the error icon **\(\mathbf{A} \)** will be displayed under the temperature.

- 18. <u>Panel Com Error:</u> The topside controller is having trouble communicating to your spa. Contact your authorized dealer or service organization.
- 19. <u>Stereo Com Error:</u> The stereo is having trouble communicating to your spa. Contact your authorized dealer or service organization.

- 20. Wi-Fi Com Error (50Hz models only): The Wi-Fi module is having trouble communicating to your spa. Contact your authorized dealer or service organization.
- 21. CLEARRAY Replacement Reminder: This message will appear when the CLEARRAY bulb reminder time has expired (Figure 15.0c). The CLEARRAY bulb must be replaced.
- 22. MicroClean Outer Filter Reminder: This message will appear when the filter reminder time has expired (Figure 15.0d). Remove the MicroClean Outer filters for cleaning or replacement.
- 23. MicroClean Inner Filter Reminder: This message will appear when the filter reminder time has expired (Figure 15.0e). The MicroClean Inner filter must be replaced.
- Water Refresh Reminder: This message will appear when the "Water Refresh" timer has expired (Figure 15.0f). The water needs to be drained and refilled with fresh water.
- 25. Extended Temperature Activated: The spa is set to Reset go up to 104°F (40°C), but it can be set to reach 106°F (41°C). To access the extended temperature you need press and hold your finger over the temperature reading for about 5 seconds. The temperature reading will start to blink to indicate the system is ready. Tap \triangle to raise the temperature up to 106°F (41°C).

Note: The heater icon **\(\lambda \)** will be blinking to indicate that the feature is active.



WARNING: RISK OF HYPERTHERMIA (OVER-HEATING) CAUSING SEVERE INJURY, BURNS, WELTS OR DEATH! Water temperature in excess of 104°F (40°C) may be injurious to your health.



Figure 15.0c



Figure 15.0d



Figure 15.0e



Figure 15.0f

16.0 Troubleshooting - Procedures

In the unlikely event your hot tub is not working the way you believe it should, please first review all the installation and operating instructions in this manual and check the message on the panel display; second, if you are still not satisfied it is working properly, please follow the appropriate troubleshooting instructions.

PROBLEM

PROCEDURE

None of the components operate (i.e. pump, blower, light)

Check the control panel lights.

- 1. If there are letters or symbols displayed on the screen, refer to the previous section to determine meaning and action required.
- 2. If nothing appears on the screen:
 - A. Check the household circuit breaker.
 - B. Contact you Sundance Spas dealer or qualified service technician.

Pump does not operate and icon does

Depress JETS Button.

- If no sound is detected or if a buzzing sound is detected, turn off power to the spa and contact your authorized dealer or qualified service technician.
- If motor operates, but now water flows to jets:
 - Pump may not be properly primed. See instructions below.
 - B. Contact your Sundance Spas dealer or qualified service technician.

AIR LOCK

Purge "air lock" from circulation pump intake by removing filter cartridge. Hold your garden hose over the filter cartridge wall fitting while using a rag as a seal around hose end. Ask a helper to turn on water for 30 seconds, then turn off. Reinstall filter cartridge and check spa.

Pump Priming Instructions:

This method must be used for the jets pumps because these pumps are not connected to the main filter system in any way.

- 1. Turn off the power to the spa.
- Remove the handle from the massage selector supplied by the pump you are priming.
- 3. Loosen the massage selector's cap slightly (counterclockwise), listening for the air to seep out.
- 4. Tighten the cap finger tight, replace the handle, and turn the spa's power back on.

CAUTION: If freezing conditions exist and pump is not operational, take measures to protect the system from freeze damage. See Section titled "Winterizing," page 76.

Filter/ circulation pump off

- 1. Verify filter/circulation pump is programmed to run 8 hours a day (page 59).
- 2. Hot tub water is warmer than 95°F (35°C) and 2°F (1°C) warmer than the set temperature. The "Summer Logic" safety feature has activated.

PROBLEM PROCEDURE

Poor jet action (Sections 9.1-9.22, pages

22-40)

- 1. Make certain the jets pump is turned on.
- 2. Check position of massage selectors.
- 3. Open air control for selected jet system.
- 4. Check for adequate water level.
- 5. Check for dirty filter (pages 69-71).

Water is too hot

- 1. Reduce thermostat setting (page 18).
- 2. Switch hot tub to "Economy" mode to turn heater on only during programmed filter cycles (page 58).

No heat


- 1. Check thermostat setting.
- 2. Keep the cover in place while heating.
- If "heater on" indicator is lit but no temperature rise is experienced after a reasonable period of time, contact your Sundance Spas dealer or qualified service technician.


Should checking the above steps fail to correct the problem, please call your authorized dealer so that he may arrange service.

Sundance builds the best hot tubs in the industry. Nonetheless, we are always striving to improve the quality and features of our products. Your input as a Sundance hot tub owner is a cherished part of this process. If you have any comments or suggestions, or if you wish to be informed on any new products for your hot tub, please write to us.

CONGRATULATIONS on your good taste and welcome to the happiest and most relaxed family in the world!

17.0 Typical Hot Tub Wiring Diagrams A-B (North American 60 Hz Models Only)









18.0 North American 60 Hz Electrical Wiring Diagram

18.1 North American 60 Hz 3-Pump Models Electrical Wiring Diagram




18.2 North American 60 Hz 1- and 2-Pump Models Electrical Wiring Diagram



18.3 Dip Switch Settings

The dip switches are at the S1 location on the board.

A. Switch settings for Domestic 60Hz Models



BREAKER	DIP SWITCH NUMBER									
	1	2	3	4	5	6	7	8	9	10
40A	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF
50A*	OFF	OFF	ON	OFF						
60A**	OFF	OFF	OFF	ON	OFF	OFF	OFF	OFF	OFF	OFF

^{*50}A is the factory default setting for 1- and 2-pump models

880 1- and 2-pump Service Jumper Wiring				
Wire	From	То		
1	J37	J36		
2	J51	J46		
3	J59	J41		
4	J44	J49 & J35		
5	J33	J47		
6	J4	J58		
7	J3	J45		

880 Maxxus and Aspen Service Jumper Wiring				
Wire	From	То		
1	J37	J36		
2	J51	J46		
3	J59	J41		
4	J44	J49 & J35		
5	J33	J47		
6	J61	J45		
7	J65	J40		
8	J4	J58		
9	J3	J32		

^{**60}A is the factory default setting for 3-pump models